

# MICRO 5



















QUICK REFERENCE



# MICRO 5 QUICK REFERENCE

## SMALL LINEAR FIXTURES

 Lumens/ft: Up to 323 at 4.0W/ft  
 Color Temperature: 2000K-5500K  
 CRI: Up to 98  
 Color: SW, DW-HE, RGB  
 Options comply with Buy American Act  
 **Declare.** Red List Approved  
 All MICRO 5 fixtures have Declare labels and are Red List Approved

	FLAT LENS	OPTICAL LENS	ENCAPSULATED	DROP LENS
<b>MICRO 5 ALTA</b> Low-profile with magnet mount installation .44"W X .43"H 120°	 .44"W X .43"H 120°	 .44"W X .57"H 30°	 .44"W X .43"H	 .44"W X .63"H 113°
<b>MICRO 5 ATOM</b> Low-profile surface mount .44"W X .37"H 120°	 .44"W X .37"H 120°	 .44"W X .51"H 20°	 .44"W X .37"H	
<b>MICRO 5 TILT</b> Sleek flat 45° angled .44"W X .44"H 120°	 .44"W X .44"H 120°			
<b>MICRO 5 SLITE</b> Two piece mud-in fixture 2.08"W X .44"H 120°	 2.08"W X .44"H 120°		 2.08"W X .44"H	
<b>MICRO 5 KICKER</b> Recessable with asymmetrical direction .71"W X .41"H 110°	 .71"W X .41"H 110°		 .71"W X .41"H	
<b>MICRO 5 POP</b> Recessable with an 80° focused beam 20° off-nadir .45"W X .47"H 90°	 .45"W X .47"H 90°		 .45"W X .47"H	
<b>MICRO 5 POP MUD-IN</b> For flush installations 1.66"W X .62"H 90°	 1.66"W X .62"H 90°		 1.66"W X .62"H	
<b>MICRO 5 POP FLANGE</b> Recessable and flanged with a 75° focused beam 20° off-nadir .69"W X .53"H 75°	 .69"W X .53"H 75°		 .69"W X .53"H	

Diagrams not to scale

▲ Beam angle

Diode Visibility

