OPTI

QUICK REFERENCE



QTL.lighting

OPTI QUICK REFERENCE

OPTICAL LINEAR FIXTURES

Lumens/ft:
Up to 906
at 9.0W/ft






Color
Temperature:
1800K-5500K






CRI:
Up to 98

Color:
SW, SW-HE, DW-HE,
SC, RGB, RGBW,
RGBW-HE

Options comply with
BAA, BABA

All OPTI fixtures have
EPDs, Declare labels, and
are Red List Approved

	PROFILE
OPTI-FLAT (01)	 DF FR PR 1.00"W X .53"H 99°-115°
OPTI-OPTICS (02) 40°	 OPTIC 1.00"W X .57"H 40°
OPTI-OPTICS (02) 60°	 OPTIC 1.00"W X .57"H 60°
OPTI-OPTICS (02) 70°	 OPTIC 1.00"W X .56"H 70°
OPTI-OPTICS (02) 90°	 OPTIC 1.00"W X .54"H 90°

	PROFILE
OPTI-OPTICS (02) 110°	 OPTIC 1.00"W X .57"H 110°
OPTI-OPTICS (02) 155°	 OPTIC 1.00"W X .65"H 155°
OPTI-OPTICS (02) 180°	 OPTIC 1.00"W X .79"H 180°
OPTI-OPTICS (02) ASYMMETRIC	 OPTIC 1.00"W X .57"H 46° SHIFTED 25° OFF CENTER
OPTI-OPTICS (02) FORWARD THROW	 OPTIC 1.00"W X .68"H 70° SHIFTED 41° OFF CENTER

Diagrams not to scale

Nominal beam angle

Diode Visibility



Frosted Polar Diffused Optical