

# NL-LARGE

L BRACKET - ALUMINUM EXTRUSION

RoHS COMPLIANT






- L bracket with no reveal, creating the least amount of cutoff
- Surface mounts from the side, best for wall applications
- Mounts a large family of fixtures, LED light engines, and SHIELD
- Paintable finish
- Intended for indoor use only
- Screw mounting track for field installation of fixtures
- Inline bracket slot for seamless run connections
- Durable anodized aluminum

| 1 PRODUCT | 2 FINISH | 3 LENGTH (IN) |
|---|---|---|
| **NL-LARGE** | | |

Sample Part Number: **NL-LARGE-ST-48"**

**1 PRODUCT**

| |
|---|
| **NL-LARGE** |


**2 FINISH**

| | |
|---|---|
| **ST** | Satin |
| **BK** | Black |


**3 LENGTH (IN)**

1" increments from 2" - 98.43"
Tolerance +0.0"/-0.5"
Light engine ordered separately


## 1 PRODUCT - DIMENSIONS WITH RECOMMENDED PROFILES





Profile





Profile with: OPTI-02 FT lens





Profile with: VEVE-01




Profile with: TORQ-01




Profile with: VERS-09




Profile with: ARKA-01

Field modifications must comply with Q-Tran's installation methods otherwise warranty is null & void | Corner/surface mount

© 2024 QTL. All rights reserved | 155 Hill St. Milford, CT 06460 | 203-367-8777 | sales@QTL.lighting | www.QTL.lighting

Specification subject to change. Rev-03-12-24

# NL-LARGE






L BRACKET - ALUMINUM EXTRUSION

## 2 FINISH

Satin

Black

## COMPATIBILITY CHART

| |  ARKA |  TELA |  VEVE |  OPTI |  VERS |  TORQ |  BOXA |  KURV |  ZALA |
|---|---|---|---|---|---|---|---|---|---|
| Lens Notes | Works with: ARKA-01 | Works with: TELA-01 | Works with: VEVE-01, VEVE-03 | Works with: 40D lens, 60D lens, 70D lens, 90D lens, 110D lens, 155D lens, ASYM lens, FT Lens | Works with: VERS-01, VERS-02, VERS-03, VERS-05, VERS-06, VERS-07, VERS-08, VERS-09 | Works with: TORQ-01, TORQ-03 | | | |
| SST-01 Stainless Steel Clip | | | ✓ | ✓ | | ✓ | | | |
| SST-03 Stainless Steel Clip | ✓ | ✓ | | | | | | | |
| CC-01 Concealed Clip | | | | | ✓ | | | | |
| WSC White Snug Clip | | | | | | | ✓ | ✓ | ✓ |
| VHB | ✓ | ✓ | ✓ | | | ✓ | ✓ | ✓ | ✓ |

© 2024 QTL. All rights reserved | 155 Hill St. Milford, CT 06460 | 203-367-8777 | sales@QTL.lighting | www.QTL.lighting


# NL-LARGE

L BRACKET - ALUMINUM EXTRUSION

## PHOTOMETRIC PERFORMANCE

Order separately | Tested with SW24/5.0 at 3000K

116.2°







BOXA

| LENS | LM/FT | CCT |
|---|---|---|
| ENC/TL | 218 | 3000K |

118.6°







KURV

| LENS | LM/FT | CCT |
|---|---|---|
| ENC/TL | 232 | 3000K |

102.8°







TORQ

| LENS | LM/FT | CCT |
|---|---|---|
| DF | 226 | 3000K |

111.1°







VERS

| LENS | LM/FT | CCT |
|---|---|---|
| DF | 302 | 3000K |

33.6°







VERS

| LENS | LM/FT | CCT |
|---|---|---|
| ASYM | 307 | 3000K |

112.1°







VEVE

| LENS | LM/FT | CCT |
|---|---|---|
| DF | 278 | 3000K |

117.8°







ZALA

| LENS | LM/FT | CCT |
|---|---|---|
| ENC/TL | 205 | 3000K |

59.4°







OPTI

| LENS | LM/FT | CCT |
|---|---|---|
| FT | 269 | 3000K |

## JOINER/CONNECTORS



Inline Bracket

1 per length included

6/32" stainless steel, flat tip set screws, 1/8" long

© 2024 QTL. All rights reserved | 155 Hill St. Milford, CT 06460 | 203-367-8777 | sales@QTL.lighting | www.QTL.lighting