
EXCELSIOR IN-10

12V MR16 35W Halogen/8W LED In Ground Well Light



IN-10 Shown in Bronze Texture Powder Coat Finish (BZT)



Dimensions: 6 5/8" dia. x 11 1/4" tall

- 6061 Marine Grade Aluminum. Eight standard TGIC Free powder coat finishes
- 15 degrees of aiming adjustment.
- Machined aluminum lamp holder.
- Tempered glass lens.
- 6' of 16/2 low voltage cable supplied.
- Maximum Wattage: 35W Halogen/8W LED
- Input Voltage: 12V (remote transformer required)
- Socket: GU5.3 Bi Pin Porcelain
- Wet Listed
- Specification-grade, wet-location direct burial landscape luminaire for uplighting applications.
- UL Listed for USA market

1 PRODUCT	2 MATERIAL	3 FIXTURE REGRESS	4 FINISH
IN-10	A		

Sample Part Number: **IN-10-A-1-NT**

1 PRODUCT

IN-10	

2 MATERIAL

A	Aluminum

3 FIXTURE REGRESS

1	1 3/4" Regress
2	3" Regress (standard)

4 FINISH

BG	Beige
BB	Black Bronze
BK	Black
BKT	Black Texture
BZ	Bronze
BZT	Bronze Texture
SL	Silver
WH	White

5 year warranty | Warranty only valid with QTL power supplies | Field modifications void warranty | Data subject to change, all data has +/- 5% tolerance


© 2026 QTL. All rights reserved | 155 Hill St. Milford, CT 06460 | 203-367-8777 | sales@QTL.lighting | www.QTL.lighting

Specification subject to change. Rev-09-28-26

EXCELSIOR IN-10

12V MR16 35W Halogen/8W LED In Ground Well Light

1 PRODUCT - DIMENSIONS



2 MATERIAL

Aluminum

4 FINISH

Eight Standard TGIC Free powder coat finishes

Beige

Black

Black Texture

Bronze

Bronze Texture

Black Bronze

Silver

White

ACCESSORIES - LENS

Holds up to three accessories

SP



Spread Lens

To order separately use AY-1-MR16-1


LI



Linear Lens

To order separately use AY-1-MR16-2

SO



Softening Lens

To order separately use AY-1-MR16-3

LV



Louver Lens

To order separately use AY-1-MR16-4

WI



Wire Holder

To order separately use AY-1-MR16-5

FR



Frosted Lens

To order separately use AY-1-MR16-6

© 2026 QTL. All rights reserved | 155 Hill St. Milford, CT 06460 | 203-367-8777 | sales@QTL.lighting | www.QTL.lighting

Specification subject to change. Rev-09-28-26

EXCELSIOR IN-10

12V MR16 35W Halogen/8W LED In Ground Well Light

LAMPS

MR16 Halogen or LED; GU5.3 Bi Pin Porcelain
Maximum wattage: 35W Halogen/8W LED

MR16



EMERY ALLEN

1.0W, 3.0W, 5.0W, 7.0W, 8.0W

MR16



EMERY ALLEN

3W AMBER

COMPATIBLE POWER SUPPLIES

See power supplies cut sheets for more information. Data subject to change, all data has +/- 5% tolerance.

DIMMING PROTOCOL	OUTDOOR
	LANDSCAPE LIGHTING
Phase	Q-HEX Q-SET-1 Q-SET-2 Q-SET-3 QOMD QOMS

© 2026 QTL. All rights reserved | 155 Hill St. Milford, CT 06460 | 203-367-8777 | sales@QTL.lighting | www.QTL.lighting