# Q-CAP LUME-01 STATIC WHITE

24VDC Flexible Fixtures






- Flexible encapsulated fixture
- Three-sided illumination
- Up/down bend
- 6" bend radius
- Interior and exterior rated (not including FC)
- Available in a seamless configuration for a continuous line of light
- Three different mounting options
- Do not cut Non-Field Cuttable Q-CAP flexible fixtures

## ORDERING PROCESS

(A) Specify Non-Field Cuttable Q-CAP

(B) (Optional) Specify field cuttable 4' piece - used to adjust total run length in the field (dry applications only)

## A. NON-FIELD CUTTABLE Q-CAP

**INFORMATION REQUIRED FOR LIGHTING SCHEDULE**

| A1 | A2 | A3 | A4 | A5 | A6 |
|---|---|---|---|---|---|
| PRODUCT | MOUNTING | RATED | CCT | WATTAGE | LENS |
| | | | | | ENC/TL |

**ADDITIONAL INFORMATION REQUIRED TO ORDER**

| A7 | A8 | A9 | A10 | A11 | A12 |
|---|---|---|---|---|---|
| WIRE INPUT/ OUTPUT | CONNECTOR/ WIRE IN | CONNECTOR/ WIRE OUT | END CAPS | LENGTH (IN) | EXACT/ OPTIMAL |
| | | | TL | | |

Sample Part Number: **LUME-01-SW-MC-DRY-30-5.0-ENC/TL-P1-BW-BW-N/A-48"-E**

### A1 PRODUCT

**LUME-01-SW**
**LUME-01-SW-USA**

Select USA option for BA, BAA and BABA projects.

See last page for compatible power supplies.

### A2 MOUNTING

| | |
|---|---|
| **MC** | Magnetic Clip |
| **PPS-LP-CL-2** | Clear PVC Clip |
| **PPS-LP-CL-96** | Clear PVC Channel |
| **WSC** | White Snug Clip |

White snug clip only for indirect cove use, not intended for hanging fixtures upside down.

### A3 RATED

| | |
|---|---|
| **DRY** | IP20 |
| **WET** | IP67 |

### A4 CCT

| | |
|---|---|
| **22** | 2200K |
| **24** | 2400K |
| **27** | 2700K |
| **30** | 3000K |
| **35** | 3500K |
| **40** | 4000K |

### A5 WATTAGE

| | |
|---|---|
| **1.5** | 1.5W-SO |
| **3.0** | 3.0W-HO |
| **5.0** | 5.0W-VHO |
| **1.5HE** | 1.5WHE-SO |
| **3.0HE** | 3.0WHE-HO |
| **6.0HE** | 6.0WHE-VHO |

SO: Standard Output
HO: High Output
VHO: Very High Output

### A6 LENS

**ENC/TL** Encapsulated in Translucent

For representation of LED visibility, see Diode Visibility section on following pages

### A7 WIRE INPUT/OUTPUT

**SINGLE (Input only)**

| | |
|---|---|
| **S1** | End Feed |
| **S5** | Seamless Feed |

**PASS THROUGH (Input/Output)**

| | |
|---|---|
| **P1** | End Feed |
| **P5** | Seamless Feed |

### A8 CONNECTOR/WIRE IN

| | |
|---|---|
| **BW** | Bare Wire (Standard 24") |
| **BRL** | Barrel |
| **CON6** | Connector 6" |
| **CON24** | Connector 24" |

BW: Standard length is 24", Max length is 120". Request custom length by writing in part number next to BW (example: BW48)

| | |
|---|---|
| **BW** | Bare Wire (Standard 24") |
| **BRL** | Barrel |
| **CON6** | Connector 6" |
| **CON24** | Connector 24" |

BW: Standard length is 24", Max length is 120". Request custom length by writing in part number next to BW (example: BW48)

### A9 CONNECTOR/WIRE OUT

| | |
|---|---|
| **N/A** | Closed End (No feed) |

| | |
|---|---|
| **BW** | Bare Wire (Standard 24") |
| **BRL** | Barrel |
| **CON6** | Connector 6" |
| **CON24** | Connector 24" |

BW: Standard length is 24", Max length is 120". Request custom length by writing in part number next to BW (example: BW48)

### A10 END CAPS

| | |
|---|---|
| **Single** → **TL** | Translucent |
| **Pass Through** → **N/A** | Not Applicable |

### A11 LENGTH (IN)

Minimum length is 12", maximum length is 191" not including end caps. Contact us for lengths under 12".
SW: Available in 1" increments.
SW-HE: Available in 2" increments.

### A12 EXACT/OPTIMAL

| | |
|---|---|
| **O** | Optimal Illumination |
| **E** | Exact Specified Length |

Exact fixtures are the exact length specified +0 -1/8". Optimal fixtures' length is rounded down with illumination end to end. See Exact/Optimal Fixture Length charts.

Up/Down Bend | Data subject to change, all data has +/- 5% tolerance | Only FC fixtures are Field-Cuttable per installation instructions | Field Cuttable is not returnable or refundable after it has been cut

© 2026 QTL. All rights reserved | 155 Hill St. Milford, CT 06460 | 203-367-8777 | sales@QTLlighting | www.QTLlighting

Specification subject to change. Rev-11-24-26

# Q-CAP LUME-01 STATIC WHITE

24VDC Flexible Fixtures

## B. FIELD CUTTABLE Q-CAP

**INFORMATION REQUIRED FOR LIGHTING SCHEDULE**

| B1 | B2 | B3 | B4 | B5 | B6 |
|---|---|---|---|---|---|
| PRODUCT | MOUNTING | RATED | CCT | WATTAGE | LENS |
| | | DRY | | | ENC/TL |

**ADDITIONAL INFORMATION REQUIRED TO ORDER**

| B7 | B8 | B9 | B10 | B11 | B12 |
|---|---|---|---|---|---|
| WIRE INPUT/ OUTPUT | CONNECTOR/ WIRE IN | CONNECTOR/ WIRE OUT | END CAPS | LENGTH (IN) | EXACT/ OPTIMAL |
| | | N/A | TL | 48” | N/A |

Sample Part Number: **LUME-01-FC-SW-MC-DRY-30-5.0-ENC/TL-S1-BW-N/A-TL-48"-N/A**

### B1 PRODUCT

**LUME-01-FC-SW**
**LUME-01-FC-SW-USA**

Select USA option for BA, BAA and BABA projects.

See last page for compatible power supplies.

### B2 MOUNTING

| | |
|---|---|
| **MC** | Magnetic Clip |
| **PPS-LP-CL-2** | Clear PVC Clip |
| **PPS-LP-CL-96** | Clear PVC Channel |
| **WSC** | White Snug Clip |

White snug clip only for indirect cove use, not intended for hanging fixtures upside down.

### B3 RATED

| | |
|---|---|
| **DRY** | IP20 |

### B4 CCT

| | |
|---|---|
| **22** | 2200K |
| **24** | 2400K |
| **27** | 2700K |
| **30** | 3000K |
| **35** | 3500K |
| **40** | 4000K |

### B5 WATTAGE

| | |
|---|---|
| **1.5** | 1.5W-SO |
| **3.0** | 3.0W-HO |
| **5.0** | 5.0W-VHO |
| **1.5HE** | 1.5WHE-SO |
| **3.0HE** | 3.0WHE-HO |
| **6.0HE** | 6.0WHE-VHO |

SO: Standard Output
HO: High Output
VHO: Very High Output

### B6 LENS

| | |
|---|---|
| **ENC/TL** | Encapsulated in Translucent |

For representation of LED visibility, see Diode Visibility section on following pages

### B7 WIRE INPUT/OUTPUT

| | |
|---|---|
| **SINGLE (Input only)** | |
| **S1** | End Feed |
| **S5** | Seamless Feed |

### B8 CONNECTOR/WIRE IN

| | |
|---|---|
| **BW** | Bare Wire (Standard 24”) |
| **BRL** | Barrel |
| **CON6** | Connector 6” |
| **CON24** | Connector 24” |

BW: Standard length is 24”, Max length is 120”. Request custom length by writing in part number next to BW (example: BW48)

### B9 CONNECTOR/WIRE OUT

| | |
|---|---|
| **N/A** | Closed End (No feed) |

### B10 END CAPS

Single

| | |
|---|---|
| **TL** | Translucent |

### B11 LENGTH (IN)

| | |
|---|---|
| **48”** | Nominal |

Starting Run length is 48.475” for S1
Each cut point subtracts from the Starting Run Length
1.5, 3.0, & 5.0 have a 1” cut point
1.5HE, 3.0HE, & 6.0HE have a 2” cut point
S1 can be cut down to as little as 1.475” for SW & 2.475” SW-HE

### B12 EXACT/OPTIMAL

| | |
|---|---|
| **N/A** | |

© 2026 QTL. All rights reserved | 155 Hill St. Milford, CT 06460 | 203-367-8777 | sales@QTL.lighting | www.QTL.lighting

# Q-CAP LUME-01 STATIC WHITE

24VDC Flexible Fixtures

## 1 PRODUCT - DIMENSIONS




Profile
(Standard)




Profile
(Seamless bare wire)




Profile
(Seamless barrel)




Profile
(CON6-24 barrel)




Seamless Omnidirectional
wireways (S5, P5)

Shown with bare wire
connectors vary

## BEND RADIUS

**Up/Down Bend**



6" bending radius

## FLEXIBILITY




## 2 MOUNTING

**WSC**




White Snug Clip
Indirect uplight

To order separately use WSC

Each clip comes with a #6x5/8" flat screw

**MC**




Magnetic Clip
Cove use only

To order separately use MC

Each clip comes with a #6x5/8" flat screw

**PPS-LP-CL-2**




Low profile PC Mounting
Clip - Clear finish

To order separately use LUME-PPS-LP-CL-2

PPS kit quantity: **(2 kits per ft) + 1.**
For example: 1 ft = (2 × 1) + 1 = 3 PPS kits provided.

**PPS-LP-CL-96**




Low profile PC channel
96" straight linear run
Clear finish

To order separately use LUME-PPS-LP-CL-96

PPS kit quantity: **(2 kits per ft) + 1.**
For example: 1 ft = (2 × 1) + 1 = 3 PPS kits provided.

Each clip comes with a #8" flat screw

© 2026 QTL. All rights reserved | 155 Hill St. Milford, CT 06460 | 203-367-8777 | sales@QTL.lighting | www.QTL.lighting

Specification subject to change. Rev-11-24-26

# Q-CAP LUME-01 STATIC WHITE

24VDC Flexible Fixtures

## 4/5 DELIVERED LUMENS

[Calculated L70 = 40000 hrs]
Tested with LUME-01-SW-WSC-DRY

| CCT | 1.5W/FT ENC/TL | | 1.5HE W/FT ENC/TL | | 3.0W/FT ENC/TL | | 3.0HE W/FT ENC/TL | | 5.0W/FT ENC/TL | | 6.0HE W/FT ENC/TL | |
|---|---|---|---|---|---|---|---|---|---|---|---|---|
| | LM | CRI | LM | CRI | LM | CRI | LM | CRI | LM | CRI | LM | CRI |
| 2200K | ** | ** | ** | ** | ** | ** | ** | ** | ** | ** | ** | ** |
| 2400K | 74 | 92 | 77 | 93 | 137 | 92 | 164 | 93 | 232 | 92 | 378 | 93 |
| 2700K | 66 | 97 | 68 | 97 | 132 | 97 | 186 | 97 | 229 | 98 | 369 | 97 |
| 3000K | 73 | 95 | 84 | 95 | 142 | 95 | 180 | 95 | 239 | 95 | 387 | 95 |
| 3500K | 82 | 98 | 82 | 97 | 155 | 98 | 178 | 97 | 225 | 98 | 394 | 97 |
| 4000K | 65 | 97 | 79 | 97 | 130 | 97 | 170 | 97 | 229 | 97 | 397 | 97 |

## 6 DIODE VISIBILITY




## TEMPERATURE RATINGS

| | 1.5 W/FT | | 1.5 HE W/FT | | 3.0 W/FT | | 3.0 HE W/FT | | 5.0 W/FT | | 6.0 HE W/FT | |
|---|---|---|---|---|---|---|---|---|---|---|---|---|
| | Min | Max | Min | Max | Min | Max | Min | Max | Min | Max | Min | Max |
| Ambient Operating Temp - Surface | -4°F | 130°F | -4°F | 140°F | -4°F | 125°F | -4°F | 125°F | -4°F | 105°F | -4°F | 95°F |
| Storage Temp | -4°F | 140°F | -4°F | 140°F | -4°F | 140°F | -4°F | 140°F | -4°F | 140°F | -4°F | 140°F |
| Installation Temp | 50°F | 100°F | 50°F | 100°F | 50°F | 100°F | 50°F | 100°F | 50°F | 100°F | 50°F | 100°F |

## BUG RATING

| WATTAGE | B | U | G |
|---|---|---|---|
| 1.5 (ALL CCTs), 1.5HE (ALL CCTs) | B0 | U1 | G0 |
| 3.0 (ALL CCTs), 5.0 (ALL CCTs), 3.0HE (ALL CCTs) | B0 | U2 | G0 |
| 6.0HE (ALL CCTs) | B0 | U2 | G1 |

## 7 WIRE INPUT/OUTPUT

SINGLE (Input only)

**S1**




End Feed

PASS THROUGH (Input/Output) - Only applicable for Non-Field Cuttable Q-CAP

**P1**




End Feed

© 2026 QTL. All rights reserved | 155 Hill St. Milford, CT 06460 | 203-367-8777 | sales@QTL.lighting | www.QTL.lighting

Specification subject to change. Rev-11-24-26

# Q-CAP LUME-01 STATIC WHITE

24VDC Flexible Fixtures

SEAMLESS SINGLE (Input only)




Seamless Feed

SEAMLESS PASS THROUGH (Input/Output) - Only applicable for Non-Field Cuttable Q-CAP




Seamless Feed

## CONFIGURATION OPTIONS




Single End Feed




Non-Continuous End Feed




Non-Continuous Corner Feed




Continuous End to End Feed




Field Cuttable - Continuous End to End Feed

## FIELD CUTTABLE MARKING




Field cuttable fixtures are sold in 4' increments and go at the end of a run, allowing for easy field adjustment




**Note:** Only FC fixtures are field cuttable — Do not attempt to cut non FC fixtures.
Cut only on the marked cut lines. Only cut from non-feed end. Do not attempt to cut while power is on.

## 8/9 CONNECTOR/WIRE – IN/OUT

Connector/Wire In or Out not needed to specify product. Typical selection is S1 for Wire Input/Output, BW for Connector/Wire In, N/A for Connector/Wire Out, and WH for End Caps




Bare Wire 24"
22 AWG




Barrel 6" - DRY/DMP | 22 AWG




Barrel 6"- WET | 22 AWG




6" or 24" Overall
Wire Connector | 22 AWG
IP67 Rated, UL Listed

© 2026 QTL. All rights reserved | 155 Hill St. Milford, CT 06460 | 203-367-8777 | sales@QTL.lighting | www.QTL.lighting

Specification subject to change. Rev-11-24-26

# Q-CAP LUME-01 STATIC WHITE

24VDC Flexible Fixtures

## 10 END CAPS (NO FEED)

TL



Translucent endcaps
.0" added at end

.00" dim spot

## 11 LENGTH - WIRING DETAIL

1.5W, 3.0W, 5.0W | Available in 1" increments 12"-191"




1.5HEW, 3.0HEW, 6.0HEW | Available in 2" increments 12"-191"




## 12 EXACT/OPTIMAL FIXTURE LENGTH

E/O Length Calculator →  E/O Explained →

Exact fixtures are the exact length specified +0 -1/8". Optimal fixtures' length is rounded down based on LED cut points to allow the fixture to be illuminated end to end. For runs with multiple fixtures that need to fill a specific length, it's recommended to order all optimal fixtures with an exact fixture at the end of the run.




## SW ENC LENGTHS BY INCH

### EXACT LENGTH

| Requested Length | Potential dim spot on either end of a S1 fixture |
|---|---|
| | S1 IN End Feed |
| 12" | 0.5" |
| 13" | 0.5" |
| 14" | 0.5" |
| 15" | 0.5" |
| 16" | 0.5" |
| 17" | 0.5" |
| 18" | 0.5" |
| 19" | 0.5" |
| 20" | 0.5" |
| 21" | 0.5" |
| 22" | 0.5" |
| 23" | 0.5" |
| 24" | 0.5" |
| 36" | 0.5" |
| 48" | 0.5" |
| 60" | 0.5" |
| 72" | 0.5" |
| 84" | 0.5" |
| 96" | 0.5" |

### OPTIMAL LENGTH

| Requested Nominal Length | S1 | P1 | S5 & P5 | |
|---|---|---|---|---|
| | S1 IN End Feed | P1 OUT IN End Feed | S5 Seamless Feed | P5 Seamless Feed |
| 12" | 11.45" | 11.70" | 11.20" | |
| 13" | 12.45" | 12.70" | 12.20" | |
| 14" | 13.45" | 13.70" | 13.20" | |
| 15" | 14.45" | 14.70" | 14.20" | |
| 16" | 15.45" | 15.70" | 15.20" | |
| 17" | 16.45" | 16.70" | 16.20" | |
| 18" | 17.45" | 17.70" | 17.20" | |
| 19" | 18.45" | 18.70" | 18.20" | |
| 20" | 19.45" | 19.70" | 19.20" | |
| 21" | 20.45" | 20.70" | 20.20" | |
| 22" | 21.45" | 21.70" | 21.20" | |
| 23" | 22.45" | 22.70" | 22.20" | |
| 24" | 23.45" | 23.70" | 23.20" | |
| 36" | 35.45" | 35.70" | 35.20" | |
| 48" | 47.45" | 47.70" | 47.20" | |
| 60" | 59.45" | 59.70" | 59.20" | |
| 72" | 71.45" | 71.70" | 71.20" | |
| 84" | 83.45" | 83.70" | 83.20" | |
| 96" | 95.45" | 95.70" | 95.20" | |

© 2026 QTL. All rights reserved | 155 Hill St. Milford, CT 06460 | 203-367-8777 | sales@QTLlighting | www.QTLlighting

Specification subject to change. Rev-11-24-26

# Q-CAP LUME-01 STATIC WHITE

24VDC Flexible Fixtures

## SW-HE ENC LENGTHS BY INCH

### EXACT LENGTH

| Requested Length | Potential dim spot on either end of a S1 fixture |
|---|---|
| |   End Feed |
| 12" | 1" |
| 13" | 0.5" |
| 14" | 1" |
| 15" | 0.5" |
| 16" | 1" |
| 17" | 0.5" |
| 18" | 1" |
| 19" | 0.5" |
| 20" | 1" |
| 21" | 0.5" |
| 22" | 1" |
| 23" | 0.5" |
| 24" | 1" |
| 36" | 1" |
| 48" | 1" |
| 60" | 1" |
| 72" | 1" |
| 84" | 1" |
| 96" | 1" |

### OPTIMAL LENGTH

| Requested Nominal Length | S1 | P1 | S5 & P5 | |
|---|---|---|---|---|
| |   End Feed |   End Feed |   Seamless Feed |   Seamless Feed |
| 12" | 10.45" | 10.70" | 10.20" | |
| 13" | 12.45" | 12.70" | 12.20" | |
| 14" | 12.45" | 12.70" | 12.20" | |
| 15" | 14.45" | 14.70" | 14.20" | |
| 16" | 14.45" | 14.70" | 14.20" | |
| 17" | 16.45" | 16.70" | 16.20" | |
| 18" | 16.45" | 16.70" | 16.20" | |
| 19" | 18.45" | 18.70" | 18.20" | |
| 20" | 18.45" | 18.70" | 18.20" | |
| 21" | 20.45" | 20.70" | 20.20" | |
| 22" | 20.45" | 20.70" | 20.20" | |
| 23" | 22.45" | 22.70" | 22.20" | |
| 24" | 22.45" | 22.70" | 22.20" | |
| 36" | 34.45" | 34.70" | 34.20" | |
| 48" | 46.45" | 46.70" | 46.20" | |
| 60" | 58.45" | 58.70" | 58.20" | |
| 72" | 70.45" | 70.70" | 70.20" | |
| 84" | 82.45" | 82.70" | 82.20" | |
| 96" | 94.45" | 94.70" | 94.20" | |

## COMPATIBLE POWER SUPPLIES

See power supplies cut sheets for more information. Data subject to change, all data has +/- 5% tolerance.

| DIM TO LEVEL | INDOOR | | OUTDOOR | |
|---|---|---|---|---|
| | SW24/1.5-4.0 | SW24/5.0, SW-HE, SW-HE+ | SW24/1.5-4.0 | SW24/5.0, SW-HE, SW-HE+ |
| Dim to Black | Q6M-DC+CAP<br>QTM-DC+CAP<br>iQ-PH+QD1 | Q6M-DC+CAP<br>QTM-DC+CAP<br>iQ-PH+QD1 | QOM-DC+CAP<br>QOM-PH | QOM-DC+CAP<br>QOM-PH |
| 0.1% | QT-CAB-QZ-PH/0-10V<br>QT-CAB-eLED+0-10V<br>QT-CAB-eLED+0-10V-AWN<br>QT-CAB-eLED+DALI-DT6<br>QT-CAB-eLED+DALI-DT6-AWN<br>QTM-eLED+0-10V<br>QTM-eLED+0-10V-AWN<br>QTM-eLED+DALI-DT6<br>QTM-eLED+DALI-DT6-AWN<br>QZ-BOWTIE+DIMMER<br>QZ-DMX<br>QZ-PRO-PH/0-10V<br>QZ-STICK-PH/0-10V<br>QZLP | QT-CAB-QZ-PH/0-10V<br>QT-CAB-eLED+0-10V<br>QT-CAB-eLED+0-10V-AWN<br>QT-CAB-eLED+DALI-DT6<br>QT-CAB-eLED+DALI-DT6-AWN<br>QTM-eLED+0-10V<br>QTM-eLED+0-10V-AWN<br>QTM-eLED+DALI-DT6<br>QTM-eLED+DALI-DT6-AWN<br>QZ-BOWTIE+DIMMER<br>QZ-DMX<br>QZ-PRO-PH/0-10V<br>QZ-STICK-PH/0-10V<br>QZLP | Q-SET-QZ-DMX<br>Q-SET-QZ-PH/0-10V<br>Q-SET-eLED+0-10V<br>QOM-eLED+0-10V<br>QOM-eLED+DALI-DT6<br>QOM-eLED+DALI-DT6-PS<br>QZ-DMX<br>QZ-PRO-PH/0-10V | Q-SET-QZ-DMX<br>Q-SET-QZ-PH/0-10V<br>Q-SET-eLED+0-10V<br>QOM-eLED+0-10V<br>QOM-eLED+DALI-DT6<br>QOM-eLED+DALI-DT6-PS<br>QZ-DMX<br>QZ-PRO-PH/0-10V |
| 1% | Q-DIM<br>QTM-eLED(E)<br>QZ-DALI-DT6 | Q-DIM<br>QTM-eLED(E)<br>QZ-DALI-DT6 | Q-SET+QZ-DALI-DT6<br>QZ-DALI-DT6 | Q-SET+QZ-DALI-DT6<br>QZ-DALI-DT6 |
| 10% | Non-Dim Power Supply with SW App Dongle | Non-Dim Power Supply with SW App Dongle | Q-HEX-mini-DC<br>Q-SET-mLED | |

© 2026 QTL. All rights reserved | 155 Hill St. Milford, CT 06460 | 203-367-8777 | sales@QTL.lighting | www.QTL.lighting

# Q-CAP LUME-01 STATIC WHITE

24VDC Flexible Fixtures

| DIMMING PROTOCOL | INDOOR | | OUTDOOR | |
|---|---|---|---|---|
| | SW24/1.5-4.0 | SW24/5.0, SW-HE, SW-HE+ | SW24/1.5-4.0 | SW24/5.0, SW-HE, SW-HE+ |
| **Non-Dim** | QT-CAB-eLED-ND<br>QTM-eLED-ND<br>QZ-ND | QT-CAB-eLED-ND<br>QTM-eLED-ND<br>QZ-ND | Q-SET-QZ-ND<br>Q-SET-eLED-ND<br>QOM-eLED-ND<br>QZ-ND | Q-SET-QZ-ND<br>Q-SET-eLED-ND<br>QOM-eLED-ND<br>QZ-ND |
| **Phase** | Q6M-DC+CAP<br>QT-CAB-QZ-PH/0-10V<br>QTM-DC+CAP<br>QTM-eLED(E)<br>QZ-BOWTIE+DIMMER<br>QZ-PRO-PH/0-10V<br>QZ-STICK-PH/0-10V<br>QZLP<br>iQ-PH+QD1 | Q6M-DC+CAP<br>QT-CAB-QZ-PH/0-10V<br>QTM-DC+CAP<br>QTM-eLED(E)<br>QZ-BOWTIE+DIMMER<br>QZ-PRO-PH/0-10V<br>QZ-STICK-PH/0-10V<br>QZLP<br>iQ-PH+QD1 | Q-HEX-mini-DC<br>Q-SET-QZ-PH/0-10V<br>Q-SET-mLED<br>QOM-DC+CAP<br>QOM-PH<br>QZ-PRO-PH/0-10V | Q-SET-QZ-PH/0-10V<br>QOM-DC+CAP<br>QOM-PH<br>QZ-PRO-PH/0-10V |
| **0-10V** | QT-CAB-QZ-PH/0-10V<br>QT-CAB-eLED+0-10V<br>QT-CAB-eLED+0-10V-AWN<br>QTM-eLED+0-10V<br>QTM-eLED+0-10V-AWN<br>QZ-PRO-PH/0-10V<br>QZ-STICK-PH/0-10V<br>QZLP | QT-CAB-QZ-PH/0-10V<br>QT-CAB-eLED+0-10V<br>QT-CAB-eLED+0-10V-AWN<br>QTM-eLED+0-10V<br>QTM-eLED+0-10V-AWN<br>QZ-PRO-PH/0-10V<br>QZ-STICK-PH/0-10V<br>QZLP | Q-SET-QZ-PH/0-10V<br>Q-SET-eLED+0-10V<br>QOM-eLED+0-10V<br>QZ-PRO-PH/0-10V | Q-SET-QZ-PH/0-10V<br>Q-SET-eLED+0-10V<br>QOM-eLED+0-10V<br>QZ-PRO-PH/0-10V |
| **Lutron Athena** | QT-CAB-eLED+0-10V-AWN<br>QT-CAB-eLED+DALI-DT6-AWN<br>QTM-eLED+0-10V-AWN<br>QTM-eLED+DALI-DT6-AWN | QT-CAB-eLED+0-10V-AWN<br>QT-CAB-eLED+DALI-DT6-AWN<br>QTM-eLED+0-10V-AWN<br>QTM-eLED+DALI-DT6-AWN | | |
| **ECO System** | QTM-eLED(E) | QTM-eLED(E) | | |
| **DMX** | QZ-DMX | QZ-DMX | Q-SET-QZ-DMX<br>QZ-DMX | Q-SET-QZ-DMX<br>QZ-DMX |
| **DALI-2: DT6** | QT-CAB-eLED+DALI-DT6<br>QT-CAB-eLED+DALI-DT6-AWN<br>QTM-eLED+DALI-DT6<br>QTM-eLED+DALI-DT6-AWN<br>QZ-DALI-DT6 | QT-CAB-eLED+DALI-DT6<br>QT-CAB-eLED+DALI-DT6-AWN<br>QTM-eLED+DALI-DT6<br>QTM-eLED+DALI-DT6-AWN<br>QZ-DALI-DT6 | Q-SET+QZ-DALI-DT6<br>QOM-eLED+DALI-DT6<br>QZ-DALI-DT6 | Q-SET+QZ-DALI-DT6<br>QOM-eLED+DALI-DT6<br>QZ-DALI-DT6 |
| **SCENE App Dimmed** | Non-Dim Power Supply with SW App Dongle | Non-Dim Power Supply with SW App Dongle | | |

## COMPATIBLE MOUNTING ACCESSORIES

**Q-ANGLE**




Adjustable mounting accessory

**iQ-QCAP-UNV-CUTTER**



QTL recommended FC Cutter

## COMPATIBLE WIRING ACCESSORIES

**Q-mini-J**




UL Listed, miniature junction box, DRY/DMP (WET rated with silicone)

**Q-mini-J5**




UL Listed, miniature junction box, DRY/DMP (WET rated with silicone)

**BARREL-EXT**



8ft barrel cable extender DRY ONLY

**BARREL FOUR-FER**



Splits lead from one to four LED Barrel connector fixtures, DRY/DMP

**CON120-EXT**



10ft Con cable extender DRY/DMP/WET

**CON FOUR-FER**



Splits lead from one to four LED Con connectors DRY/DMP/WET

© 2026 QTL. All rights reserved | 155 Hill St. Milford, CT 06460 | 203-367-8777 | sales@QTL.lighting | www.QTL.lighting

Specification subject to change. Rev-11-24-26

# Q-CAP LUME-01 STATIC WHITE

24VDC Flexible Fixtures

## COMPATIBLE CONTROL ACCESSORIES

**SCENE APP DONGLE**




Wi-Fi or Bluetooth Connectivity

## COMPATIBLE APPS

**NFC APP**




Read and write DMX addresses and adjust voltage

© 2026 QTL. All rights reserved | 155 Hill St. Milford, CT 06460 | 203-367-8777 | sales@QTL.lighting | www.QTL.lighting

# Q-CAP LUME

Flexible Fixtures

## Mounting

NOTE: 2 white snug clips provided per first 12", 1 for each additional 12".
Other mounting styles incur additional charge, see price guide for details.

### WSC:

**WHITE SNUG CLIP**

- For indoor/outdoor use
- Surface mounting
- Stainless steel/corrosion resistant
- Discrete mounting
- White glossy finish




**MOUNTING HARDWARE**
- #6 flat screw (one provided for each clip)
- 832 Silicone (sold separately)

### MC:

**MAGNETIC CLIP**

- For indoor/outdoor use
- Steel clip
- Neodymium magnet
- Easy install
- Easily detachable
- For inaccessible locations such as cove area
- White glossy finish




**MOUNTING HARDWARE**
- #6 flat screw (one provided for each clip)
- 832 Silicone (sold separately)

### LUME-PPS-LP-CL-2:

**PC LOW PROFILE MOUNT CLIP**

- Clear Polycarbonate (PC)
- For indoor/outdoor use
- Surface mounting
- No wire way
- Can be mounted with or without PPS-BRACKET (**COVE FRIENDLY**)







**MOUNTING HARDWARE**
- #8 Flat head screw (1 screw for every 16")
- 832 Silicone (sold separately)

### LUME-PPS-LP-CL-96 & LUME-PPS-LP-CL-FT:

**PC LOW PROFILE MOUNT CHANNEL**

- Clear Polycarbonate (PC)
- 96" (**PPS-LP-CL-96**) or custom length (**PPS-LP-CL-FT**)
- For indoor/outdoor use
- Surface mounting
- Low profile mounting
- No wire way
- Can be mounted with or without PPS-BRACKET (**COVE FRIENDLY**)







**MOUNTING HARDWARE**
- #8 Flat head screw (1 screw for every 16")
- 832 Silicone (sold separately)

© 2024 QTL. All rights reserved | 155 Hill St. Milford, CT 06460 | 203-367-8777 | sales@QTL.lighting | QTL.lighting

# Q-CAP LUME

Flexible Fixtures

## Mounting Accessories




### Q-ANGLE

**(Full ordering guide and installation available for this product in the accessories section of website)**

- Offset lighting to illuminate signs, artwork, etc.
- For indoor/outdoor use
- Wall, ceiling, or floor mounted
- Anodized aluminum/corrosion resistant
- Free moving rotating head which can be locked into specific angles
- Preset dial notches for easy adjustments from 90° to 270°

90° BACK VIEW




180° BACK VIEW




BASE; BOTTOM VIEW




### MOUNTING HARDWARE

- White Snug Clip
- 6-32 Fillister head screw
- 4-40 Flat head screw
- Drywall anchor (not provided)
- #6- 1¼ " wood screw




**Q-ANGLE MUST BE MOUNTED EVERY 12"**

SEE Q-ANGLE INSTALL FOR MORE INFORMATION

© 2024 QTL. All rights reserved | 155 Hill St. Milford, CT 06460 | 203-367-8777 | sales@QTL.lighting | QTL.lighting

# LUME

Q-CAP HANDLING INSTRUCTIONS

## WARNING: FRAGILE

**Flexible fixtures contain sensitive electronics, requiring careful handling and installation to preserve their warranty. When unpacking flexible fixtures, handle them gently and test all fixtures upon receiving.**



Keep the fixtures flat and supported when removing them from the box. Unroll them carefully on a flat surface and do not bend them against the intended bend direction.




This LUME fixture can only be up and down bent. Do not bend the fixture more than a 6" radius.



Powering the fixtures prior to installing will warm them up and make them more flexible, preventing damage.



Only FC fixtures are field cuttable. Do not attempt to cut non-FC fixtures. Field modifications void warranty.



Do not let any portion of the fixture hang in any direction during installation. Use two people to install to ensure the fixture does not hang.



Do not grab or pull by the wire feeds.




Do not bend the fixture more than 15 degrees when installing into mounting brackets or channels.

## MISHANDLING OF FIXTURES DURING INSTALLATION VOIDS WARRANTY

### TEMPERATURE RATINGS

| Static White & Static White HE | 1.5 W/FT | | 1.5HE W/FT | | 3.0 W/FT | | 3.0HE W/FT | | 5.0 W/FT | | 6.0HE W/FT | |
|---|---|---|---|---|---|---|---|---|---|---|---|---|
| | Min | Max | Min | Max | Min | Max | Min | Max | Min | Max | Min | Max |
| Ambient Operating Temp - Surface | -4°F | 130°F | -4°F | 140°F | -4°F | 125°F | -4°F | 125°F | -4°F | 105°F | -4°F | 95°F |
| Storage Temp | -4°F | 140°F | -4°F | 140°F | -4°F | 140°F | -4°F | 140°F | -4°F | 140°F | -4°F | 140°F |
| Installation Temp | 50°F | 100°F | 50°F | 100°F | 50°F | 100°F | 50°F | 100°F | 50°F | 100°F | 50°F | 100°F |

| Static Color | 5.0 W/FT | |
|---|---|---|
| | Min | Max |
| Ambient Operating Temp - Surface | -4°F | 105°F |
| Storage Temp | -4°F | 140°F |
| Installation Temp | 50°F | 100°F |

| Tunable & Warm Dim | DW 1.5HE W/FT | | DW 2.5HE W/FT | |
|---|---|---|---|---|
| | Min | Max | Min | Max |
| Ambient Operating Temp - Surface | -4°F | 140°F | -4°F | 125°F |
| Storage Temp | -4°F | 140°F | -4°F | 140°F |
| Installation Temp | 50°F | 100°F | 50°F | 100°F |

| RGB | 5.0 W/FT | |
|---|---|---|
| | Min | Max |
| Ambient Operating Temp - Surface | -14°F | 90°F |
| Storage Temp | -4°F | 140°F |
| Installation Temp | 50°F | 100°F |

© 2025 QTL. All rights reserved | 155 Hill St. Milford, CT 06460 | 203-367-8777 | sales@QTL.lighting | QTL.lighting

# Q-CAP LUME-01

Q-CAP Flexible Fixtures Installation Instructions

## ATTENTION: Please read all instructions BEFORE installation

- Product to be installed by a licensed electrician - Field modifications void warranty
- Use only with Class 2 power supply unit — Warranty only valid with QTL power supplies
- Surface mount or recessed in millwork
- Not rated for walkover
- Input Voltage: 24VDC
- Diagrams for representation only and not to scale.

## METHODS OF INSTALLATION




### Mounting Method

- WSC (page 6)
- MC (page 7)
- PPS-LP-CL-2 (page 8)
- PPS-LP-CL-96 (page 9)



© 2026 QTL. All rights reserved | 155 Hill St. Milford, CT 06460 | 203-367-8777 | sales@QTL.lighting | QTL.lighting

# Q-CAP LUME-01

Q-CAP Flexible Fixtures Installation Instructions




LUME Profile




LUME Profile
(Seamless BW)




LUME Profile
(Seamless BRL)




LUME Profile
(Seamless CON24
SW, SC)




LUME Profile
(Seamless CON24
DW-HE)




LUME Profile
(Seamless CON24
RGB)

## COMPONENTS & HARDWARE

Alternate screw lengths can be used in installation as long as the screw diameter size is consistent with the included screw diameter size

### MOUNTING CLIP & MOUNTING CHANNEL

#### WSC




White snug clip

**Included**

- #6 Flat Screw (one provided for each clip)

- White snug clip included with side graze channel
- 2 white snug clips provided per first 12", 1 for each additional 12".Other mounting styles incur additional charge, see price guide for details

#### MC




Magnetic clip
(Cove use only)

**Included**

- #6 Flat Screw (one provided for each clip)

### SEAMLESS MOUNTING CLIP & SEAMLESS MOUNTING CHANNEL

#### PPS-LP-CL-2




Low profile
PVC mounting clip

**Included**

- #8 flat head screw (one provided for each clip)
- No wireway

- Join two fixtures together
- PPS kit quantity: **(2 kits per ft) + 1**. For example: 1 ft = (2 × 1) + 1 = 3 PPS kits provided.

#### PPS-LP-CL-96




Low profile
PVC channel

**Included**

- #8 flat head screw (1 screw for every 16")
- No wireway

- Support the fixtures
- PPS kit quantity: **(2 kits per ft) + 1**. For example: 1 ft = (2 × 1) + 1 = 3 PPS kits provided.

### ACCESSORIES SOLD SEPARATELY

**Q-ANGLE;** sold in pairs




Q-ANGLE

**Included**

- 4 SS #6×1.25" Flat head wood screws
- 2 SS 4-40 Flat head clip screws
- 2 SS 6-32 Fillister screws



© 2026 QTL. All rights reserved | 155 Hill St. Milford, CT 06460 | 203-367-8777 | sales@QTL.lighting | QTL.lighting

## CONFIGURATION OPTIONS







Single End Feed




Non-Continuous End Feed




Non-Continuous Corner Feed




Continuous End to End Feed




Field Cuttable - Continuous End to End Feed

Review wire method to ensure clean installation prior to mounting finished fixture.

**NOTE:** Additional wire methods include:
S1: Connector/Wire Input only
P1: Connector/Wire Input and Output



© 2026 QTL. All rights reserved | 155 Hill St. Milford, CT 06460 | 203-367-8777 | sales@QTL.lighting | QTL.lighting

## FIELD CUTTABLE

- Field cuttable fixtures are sold in 4' increments and go at the end of a run, allowing easy field adjustment
- Only FC fixtures are field cuttable - DO NOT CUT NON-FIELD CUTTABLE FIXTURES
- Do not attempt to cut while power is on







Mark desired length on field cuttable housing on the cut line.

**NOTE:** Only Cut on the marked cut lines. Only cut from non-feed end.




Cut with Q-CAP cutter tools (sold separately).



© 2026 QTL. All rights reserved | 155 Hill St. Milford, CT 06460 | 203-367-8777 | sales@QTL.lighting | QTL.lighting

## SURFACE MOUNTING METHOD: **WHITE SNUG CLIP**

- 2 clips provided per first 12", 1 for each additional 12"




Determine the fixture(s) location and positioning on desired surface; evenly distribute clips. Make any necessary reference markings to indicate where each clip is to be secured in place. Recommended every 12".




- Secure clips using the #6 flat head hardware provided
- Ensure the screw head is flush with the clip's base.

**NOTE:** Flat head screw type is dependent on surface/application material Alternative flat head screws may be required. Refer to the surface material manufacturer for suggested screw type.




Snap fixture onto clips.



© 2026 QTL. All rights reserved | 155 Hill St. Milford, CT 06460 | 203-367-8777 | sales@QTL.lighting | QTL.lighting

# Q-CAP LUME-01

Q-CAP Flexible Fixtures Installation Instructions

## MOUNTING METHOD: **MAGNETIC CLIP**

- 2 clips provided per first 12", 1 for each additional 12"




Determine the fixture(s) location and positioning on desired surface; evenly distribute clips. Make any necessary reference markings to indicate where each clip is to be secured in place. Recommended every 12".




Attach clips to fixture matching magnet distances.

**NOTE:** Flat head screw type is dependent on surface/application material. Alternative flat head screws may be required. Refer to the surface material manufacturer for suggested screw type.




Align and snap fixture to magnetic rings.



© 2026 QTL. All rights reserved | 155 Hill St. Milford, CT 06460 | 203-367-8777 | sales@QTL.lighting | QTL.lighting

## SEAMLESS MOUNTING METHOD: **PPS-LP-CL-2**

- Connects two fixtures, with no wire exit
- 2" low profile PVC mount channel




Snap in 2" channel.




Press fixture into mounted PPS channel.




Finished assembly for end feed mounting



© 2026 QTL. All rights reserved | 155 Hill St. Milford, CT 06460 | 203-367-8777 | sales@QTL.lighting | QTL.lighting

SEAMLESS MOUNTING METHOD: **PPS-LP-CL-96**

- Support two fixtures, without built-in wireway
- 96" (PPS-LP-CL-96) low profile PVC mount channel




The PPS-BRACKET can be field cuttable and cut to whatever length your application requires. The PPS-BRACKET can be installed as a full length of 96", multiple smaller pieces, or end to end for longer seamless runs.

Using pre-drilled pilot holes screw the #8 flat head screws to mount the PPS-BRACKET (1 screw every 16").

**NOTE:** For drywall applications mount directly into a stud.




Using pre-drilled pilot holes, use the #8 flat head screws to mount the PPS-BRACKET.




To mount, pinch the upper half of the PPS-LP-CL-96 while you pivot it around one side of the PPS-BRACKET and push-in until you hear it snap into place. The PPS-LP-CL-96 flexes around the PPS-BRACKET to create a solid, and secure snap on connection.



© 2026 QTL. All rights reserved | 155 Hill St. Milford, CT 06460 | 203-367-8777 | sales@QTL.lighting | QTL.lighting

# Q-CAP LUME-SW(01)

Flexible Fixtures Color Data

## LUME-01-SW-DRY-24-1.5-ENC/TL

2429 K

**CRI:** 92.1

**CRI R9:** 63.7

**TM30 Rf:** 91.6

**TM30 Rg:** 100.6

**CQS:** 88.0

**X:** 0.486

**Y:** 0.418

**U:** 0.276

**V:** 0.356

**Δuv:** 0.0012










| R1 | R2 | R3 | R4 | R5 | R6 | R7 | R8 | R9 | R10 | R11 | R12 | R13 | R14 | R15 |
|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|
| 92.7 | 94.5 | 93.7 | 93.3 | 91.2 | 93.0 | 94.0 | 84.2 | 63.7 | 85.0 | 93.3 | 78.7 | 93.0 | 95.0 | 89.0 |
| **Q1** | **Q2** | **Q3** | **Q4** | **Q5** | **Q6** | **Q7** | **Q8** | **Q9** | **Q10** | **Q11** | **Q12** | **Q13** | **Q14** | **Q15** |
| 86.5 | 93.4 | 85.9 | 86.2 | 87.9 | 86.4 | 85.9 | 89.5 | 93.7 | 90.5 | 89.7 | 90.4 | 90.7 | 85.3 | 85.6 |
| **C1** | **C2** | **C3** | **C4** | **C5** | **C6** | **C7** | **C8** | **C9** | **C10** | **C11** | **C12** | **C13** | **C14** | **C15** | **C16** |
| 91.9 | 92.1 | 87.5 | 92.5 | 93.8 | 93.3 | 92.8 | 94.9 | 94.8 | 90.8 | 89.0 | 89.3 | 92.1 | 87.7 | 93.1 | 88.4 |

| TM30 | | | |
|---|---|---|---|
| Hue Bin | $R_f$ | Chroma | Hue |
| 1 | 92 | -4% | -1% |
| 2 | 92 | -4% | 3% |
| 3 | 88 | -1% | 6% |
| 4 | 92 | 0% | 4% |
| 5 | 94 | 3% | 5% |
| 6 | 93 | 5% | 1% |
| 7 | 93 | 1% | -4% |
| 8 | 95 | -1% | -3% |
| 9 | 95 | -3% | -1% |
| 10 | 91 | -4% | 4% |
| 11 | 89 | 0% | 8% |
| 12 | 89 | 3% | 4% |
| 13 | 92 | 5% | -5% |
| 14 | 88 | 4% | -7% |
| 15 | 93 | 1% | -5% |
| 16 | 88 | -2% | -8% |

## LUME-01-SW-DRY-24-3.0-ENC/TL

2418 K

**CRI:** 92.1

**CRI R9:** 62.4

**TM30 Rf:** 92.0

**TM30 Rg:** 99.7

**CQS:** 88.2

**X:** 0.488

**Y:** 0.419

**U:** 0.276

**V:** 0.357

**Δuv:** 0.0015










| R1 | R2 | R3 | R4 | R5 | R6 | R7 | R8 | R9 | R10 | R11 | R12 | R13 | R14 | R15 |
|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|
| 92.4 | 94.6 | 94.7 | 93.1 | 91.1 | 93.6 | 93.7 | 83.4 | 62.4 | 85.7 | 93.2 | 79.4 | 92.8 | 95.7 | 88.5 |
| **Q1** | **Q2** | **Q3** | **Q4** | **Q5** | **Q6** | **Q7** | **Q8** | **Q9** | **Q10** | **Q11** | **Q12** | **Q13** | **Q14** | **Q15** |
| 86.6 | 93.0 | 86.6 | 86.5 | 88.2 | 87.4 | 87.4 | 90.3 | 93.8 | 91.0 | 89.1 | 89.9 | 90.3 | 84.8 | 85.5 |
| **C1** | **C2** | **C3** | **C4** | **C5** | **C6** | **C7** | **C8** | **C9** | **C10** | **C11** | **C12** | **C13** | **C14** | **C15** | **C16** |
| 91.6 | 92.1 | 88.5 | 93.4 | 94.5 | 94.6 | 94.3 | 96.4 | 94.9 | 90.7 | 89.2 | 89.9 | 91.9 | 87.5 | 93.5 | 88.2 |

| TM30 | | | |
|---|---|---|---|
| Hue Bin | $R_f$ | Chroma | Hue |
| 1 | 92 | -4% | -1% |
| 2 | 92 | -4% | 2% |
| 3 | 89 | -2% | 5% |
| 4 | 93 | -1% | 3% |
| 5 | 95 | 2% | 4% |
| 6 | 95 | 3% | 1% |
| 7 | 94 | 0% | -3% |
| 8 | 96 | -1% | -2% |
| 9 | 95 | -3% | 0% |
| 10 | 91 | -3% | 5% |
| 11 | 89 | 1% | 8% |
| 12 | 90 | 3% | 3% |
| 13 | 92 | 4% | -6% |
| 14 | 88 | 4% | -8% |
| 15 | 93 | 0% | -4% |
| 16 | 88 | -3% | -8% |

## LUME-01-SW-DRY-24-5.0-ENC/TL

2402 K

**CRI:** 92.4

**CRI R9:** 63.8

**TM30 Rf:** 91.1

**TM30 Rg:** 101.6

**CQS:** 87.3

**X:** 0.486

**Y:** 0.414

**U:** 0.278

**V:** 0.355

**Δuv:** -0.0004










| R1 | R2 | R3 | R4 | R5 | R6 | R7 | R8 | R9 | R10 | R11 | R12 | R13 | R14 | R15 |
|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|
| 93.1 | 95.5 | 95.0 | 92.9 | 91.9 | 94.5 | 92.9 | 83.5 | 63.8 | 87.2 | 93.1 | 82.8 | 93.7 | 95.8 | 89.6 |
| **Q1** | **Q2** | **Q3** | **Q4** | **Q5** | **Q6** | **Q7** | **Q8** | **Q9** | **Q10** | **Q11** | **Q12** | **Q13** | **Q14** | **Q15** |
| 85.3 | 92.9 | 85.5 | 85.9 | 87.9 | 86.0 | 83.8 | 87.1 | 94.3 | 89.6 | 89.5 | 89.7 | 90.1 | 85.7 | 85.2 |
| **C1** | **C2** | **C3** | **C4** | **C5** | **C6** | **C7** | **C8** | **C9** | **C10** | **C11** | **C12** | **C13** | **C14** | **C15** | **C16** |
| 91.6 | 91.7 | 85.9 | 91.3 | 93.0 | 91.8 | 91.1 | 93.5 | 94.8 | 91.6 | 89.8 | 89.3 | 91.3 | 86.9 | 92.3 | 88.5 |

| TM30 | | | |
|---|---|---|---|
| Hue Bin | $R_f$ | Chroma | Hue |
| 1 | 92 | -4% | -1% |
| 2 | 92 | -4% | 3% |
| 3 | 86 | -1% | 7% |
| 4 | 91 | 2% | 5% |
| 5 | 93 | 4% | 5% |
| 6 | 92 | 6% | 0% |
| 7 | 91 | 2% | -5% |
| 8 | 94 | 0% | -4% |
| 9 | 95 | -3% | -1% |
| 10 | 92 | -3% | 4% |
| 11 | 90 | 0% | 7% |
| 12 | 89 | 3% | 4% |
| 13 | 91 | 5% | -6% |
| 14 | 87 | 4% | -8% |
| 15 | 92 | 1% | -5% |
| 16 | 88 | -2% | -8% |

**NOTES:**
- CRI R values, only R1-R8 are used to calculate RA CRI values
- TM30 C values, 16 binned values out of total of 99 C values
- CQS Q values
- Data subject to change, all data has +/- 5% tolerance

© 2024 QTL. All rights reserved | 155 Hill St. Milford, CT 06460 | 203-367-8777 | sales@QTL.lighting | QTL.lighting

# Q-CAP LUME-SW(01)

Flexible Fixtures Color Data

## LUME-01-SW-DRY-27-1.5-ENC/TL

2783 K

**CRI:** 96.6

**CRI R9:** 90.8

**TM30 Rf:** 94.0

**TM30 Rg:** 101.1

**CQS:** 93.5

**X:** 0.455

**Y:** 0.412

**U:** 0.259

**V:** 0.351

**Δuv:** 0.0009










| R1 | R2 | R3 | R4 | R5 | R6 | R7 | R8 | R9 | R10 | R11 | R12 | R13 | R14 | R15 |
|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|
| 97.9 | 96.7 | 93.1 | 97.9 | 96.4 | 94.8 | 98.7 | 97.2 | 90.8 | 90.4 | 97.3 | 79.1 | 97.4 | 95.1 | 97.0 |
| **Q1** | **Q2** | **Q3** | **Q4** | **Q5** | **Q6** | **Q7** | **Q8** | **Q9** | **Q10** | **Q11** | **Q12** | **Q13** | **Q14** | **Q15** |
| 95.2 | 97.1 | 88.6 | 89.6 | 93.3 | 93.3 | 91.6 | 95.0 | 95.3 | 94.4 | 94.8 | 95.8 | 96.5 | 95.6 | 95.6 |
| **C1** | **C2** | **C3** | **C4** | **C5** | **C6** | **C7** | **C8** | **C9** | **C10** | **C11** | **C12** | **C13** | **C14** | **C15** | **C16** |
| 96.3 | 97.2 | 94.4 | 94.1 | 94.5 | 96.2 | 94.3 | 98.3 | 95.7 | 90.4 | 88.5 | 90.9 | 96.1 | 92.9 | 95.4 | 89.7 |

| TM30 | | | |
|---|---|---|---|
| Hue Bin | $R_f$ | Chroma | Hue |
| 1 | 96 | -1% | 0% |
| 2 | 97 | -1% | 0% |
| 3 | 94 | -1% | 2% |
| 4 | 94 | -2% | 1% |
| 5 | 95 | 0% | 3% |
| 6 | 96 | 2% | 1% |
| 7 | 94 | -1% | 0% |
| 8 | 98 | 0% | -1% |
| 9 | 96 | -1% | 2% |
| 10 | 90 | -1% | 6% |
| 11 | 89 | 2% | 9% |
| 12 | 91 | 4% | 4% |
| 13 | 96 | 3% | 0% |
| 14 | 93 | 5% | -3% |
| 15 | 95 | 0% | -1% |
| 16 | 90 | 2% | -8% |

## LUME-01-SW-DRY-27-3.0-ENC/TL

2776 K

**CRI:** 96.6

**CRI R9:** 90.5

**TM30 Rf:** 93.9

**TM30 Rg:** 101.5

**CQS:** 93.1

**X:** 0.454

**Y:** 0.409

**U:** 0.259

**V:** 0.351

**Δuv:** 0.0002










| R1 | R2 | R3 | R4 | R5 | R6 | R7 | R8 | R9 | R10 | R11 | R12 | R13 | R14 | R15 |
|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|
| 97.9 | 97.0 | 93.3 | 97.5 | 96.5 | 95.1 | 98.4 | 96.8 | 90.5 | 90.8 | 96.9 | 80.3 | 97.6 | 95.2 | 97.3 |
| **Q1** | **Q2** | **Q3** | **Q4** | **Q5** | **Q6** | **Q7** | **Q8** | **Q9** | **Q10** | **Q11** | **Q12** | **Q13** | **Q14** | **Q15** |
| 95.4 | 97.1 | 88.2 | 89.2 | 93.1 | 92.8 | 90.5 | 94.1 | 95.4 | 93.8 | 94.6 | 95.8 | 96.6 | 95.5 | 95.4 |
| **C1** | **C2** | **C3** | **C4** | **C5** | **C6** | **C7** | **C8** | **C9** | **C10** | **C11** | **C12** | **C13** | **C14** | **C15** | **C16** |
| 96.4 | 97.0 | 93.6 | 94.2 | 94.5 | 95.6 | 94.6 | 97.6 | 96.3 | 91.3 | 88.7 | 90.8 | 95.8 | 92.8 | 95.7 | 90.0 |

| TM30 | | | |
|---|---|---|---|
| Hue Bin | $R_f$ | Chroma | Hue |
| 1 | 96 | -1% | 0% |
| 2 | 97 | -1% | 1% |
| 3 | 94 | 0% | 3% |
| 4 | 94 | -2% | 2% |
| 5 | 94 | 0% | 3% |
| 6 | 96 | 3% | 0% |
| 7 | 95 | 0% | 0% |
| 8 | 98 | 0% | -1% |
| 9 | 96 | -1% | 1% |
| 10 | 91 | -1% | 6% |
| 11 | 89 | 1% | 8% |
| 12 | 91 | 4% | 4% |
| 13 | 96 | 3% | 0% |
| 14 | 93 | 5% | -3% |
| 15 | 96 | 0% | -1% |
| 16 | 90 | 2% | -8% |

## LUME-01-SW-DRY-27-5.0-ENC/TL

2719 K

**CRI:** 97.8

**CRI R9:** 95.7

**TM30 Rf:** 95.2

**TM30 Rg:** 102.7

**CQS:** 94.0

**X:** 0.458

**Y:** 0.408

**U:** 0.262

**V:** 0.351

**Δuv:** -0.0006










| R1 | R2 | R3 | R4 | R5 | R6 | R7 | R8 | R9 | R10 | R11 | R12 | R13 | R14 | R15 |
|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|
| 99.7 | 98.3 | 93.8 | 97.2 | 99.3 | 97.4 | 98.3 | 98.9 | 95.7 | 94.1 | 95.6 | 86.7 | 99.7 | 95.4 | 99.4 |
| **Q1** | **Q2** | **Q3** | **Q4** | **Q5** | **Q6** | **Q7** | **Q8** | **Q9** | **Q10** | **Q11** | **Q12** | **Q13** | **Q14** | **Q15** |
| 96.0 | 97.0 | 90.2 | 92.4 | 95.2 | 92.3 | 90.4 | 94.6 | 95.6 | 94.4 | 95.7 | 96.8 | 97.5 | 96.5 | 96.3 |
| **C1** | **C2** | **C3** | **C4** | **C5** | **C6** | **C7** | **C8** | **C9** | **C10** | **C11** | **C12** | **C13** | **C14** | **C15** | **C16** |
| 97.6 | 98.3 | 95.0 | 95.3 | 95.1 | 94.2 | 95.6 | 96.1 | 97.6 | 95.1 | 92.1 | 92.5 | 95.9 | 94.0 | 96.1 | 91.8 |

| TM30 | | | |
|---|---|---|---|
| Hue Bin | $R_f$ | Chroma | Hue |
| 1 | 98 | -1% | -1% |
| 2 | 98 | 0% | 0% |
| 3 | 95 | 0% | 2% |
| 4 | 95 | 0% | 2% |
| 5 | 95 | 2% | 3% |
| 6 | 94 | 4% | 1% |
| 7 | 96 | 2% | -1% |
| 8 | 96 | 1% | -2% |
| 9 | 98 | 0% | 0% |
| 10 | 95 | -1% | 3% |
| 11 | 92 | 1% | 6% |
| 12 | 93 | 4% | 2% |
| 13 | 96 | 3% | -1% |
| 14 | 94 | 4% | -2% |
| 15 | 96 | 1% | -1% |
| 16 | 92 | 2% | -6% |

**NOTES:**
- CRI R values, only R1-R8 are used to calculate RA CRI values
- TM30 C values, 16 binned values out of total of 99 C values
- CQS Q values
- Data subject to change, all data has +/- 5% tolerance

© 2024 QTL. All rights reserved | 155 Hill St. Milford, CT 06460 | 203-367-8777 | sales@QTL.lighting | QTL.lighting

Specification subject to change. Rev-03-10-24

# Q-CAP LUME-SW(01)

Flexible Fixtures Color Data

## LUME-01-SW-DRY-30-1.5-ENC/TL

3068 K

**CRI:** 94.7

**CRI R9:** 85.3

**TM30 Rf:** 92.8

**TM30 Rg:** 100.1

**CQS:** 92.8

**X:** 0.436

**Y:** 0.410

**U:** 0.247

**V:** 0.349

**Δuv:** 0.0026










| R1 | R2 | R3 | R4 | R5 | R6 | R7 | R8 | R9 | R10 | R11 | R12 | R13 | R14 | R15 |
|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|
| 95.4 | 94.8 | 92.2 | 96.1 | 93.6 | 91.8 | 98.6 | 95.2 | 85.3 | 86.2 | 95.3 | 73.0 | 94.9 | 94.8 | 94.5 |
| **Q1** | **Q2** | **Q3** | **Q4** | **Q5** | **Q6** | **Q7** | **Q8** | **Q9** | **Q10** | **Q11** | **Q12** | **Q13** | **Q14** | **Q15** |
| 94.6 | 97.6 | 87.5 | 87.7 | 91.4 | 92.3 | 92.7 | 95.7 | 95.2 | 94.1 | 93.5 | 94.6 | 95.5 | 94.4 | 95.0 |
| **C1** | **C2** | **C3** | **C4** | **C5** | **C6** | **C7** | **C8** | **C9** | **C10** | **C11** | **C12** | **C13** | **C14** | **C15** | **C16** |
| 95.0 | 95.9 | 93.5 | 94.1 | 92.5 | 96.7 | 93.9 | 97.3 | 93.6 | 86.8 | 86.0 | 90.7 | 96.1 | 92.4 | 92.9 | 89.1 |

| TM30 | | | |
|---|---|---|---|
| Hue Bin | $R_f$ | Chroma | Hue |
| 1 | 95 | -2% | 0% |
| 2 | 96 | -2% | 0% |
| 3 | 93 | -1% | 3% |
| 4 | 94 | -2% | 2% |
| 5 | 93 | -3% | 2% |
| 6 | 97 | 1% | 1% |
| 7 | 94 | -2% | 0% |
| 8 | 97 | -1% | 0% |
| 9 | 94 | -2% | 4% |
| 10 | 87 | -2% | 8% |
| 11 | 86 | 1% | 10% |
| 12 | 91 | 5% | 4% |
| 13 | 96 | 2% | 0% |
| 14 | 92 | 6% | -3% |
| 15 | 93 | 1% | -3% |
| 16 | 89 | 2% | -9% |

## LUME-01-SW-DRY-30-3.0-ENC/TL

3066 K

**CRI:** 94.6

**CRI R9:** 85.0

**TM30 Rf:** 93.0

**TM30 Rg:** 100.1

**CQS:** 92.7

**X:** 0.436

**Y:** 0.410

**U:** 0.247

**V:** 0.349

**Δuv:** 0.0025










| R1 | R2 | R3 | R4 | R5 | R6 | R7 | R8 | R9 | R10 | R11 | R12 | R13 | R14 | R15 |
|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|
| 95.2 | 94.6 | 92.1 | 95.9 | 93.4 | 91.7 | 98.4 | 95.1 | 85.0 | 85.8 | 95.1 | 73.5 | 94.7 | 94.7 | 94.3 |
| **Q1** | **Q2** | **Q3** | **Q4** | **Q5** | **Q6** | **Q7** | **Q8** | **Q9** | **Q10** | **Q11** | **Q12** | **Q13** | **Q14** | **Q15** |
| 94.8 | 97.7 | 87.5 | 87.8 | 91.3 | 92.1 | 92.5 | 95.5 | 95.2 | 94.0 | 93.4 | 94.4 | 95.4 | 94.2 | 94.9 |
| **C1** | **C2** | **C3** | **C4** | **C5** | **C6** | **C7** | **C8** | **C9** | **C10** | **C11** | **C12** | **C13** | **C14** | **C15** | **C16** |
| 95.1 | 95.9 | 93.3 | 94.2 | 92.9 | 96.6 | 94.3 | 97.4 | 94.0 | 87.2 | 86.3 | 90.9 | 96.1 | 92.7 | 93.3 | 89.6 |

| TM30 | | | |
|---|---|---|---|
| Hue Bin | $R_f$ | Chroma | Hue |
| 1 | 95 | -2% | 0% |
| 2 | 96 | -2% | 0% |
| 3 | 93 | -1% | 3% |
| 4 | 94 | -2% | 2% |
| 5 | 93 | -2% | 2% |
| 6 | 97 | 1% | 1% |
| 7 | 94 | -2% | 0% |
| 8 | 97 | -1% | 0% |
| 9 | 94 | -2% | 3% |
| 10 | 87 | -2% | 7% |
| 11 | 86 | 1% | 10% |
| 12 | 91 | 5% | 4% |
| 13 | 96 | 2% | 0% |
| 14 | 93 | 5% | -2% |
| 15 | 93 | 1% | -3% |
| 16 | 90 | 2% | -8% |

## LUME-01-SW-DRY-30-5.0-ENC/TL

3021 K

**CRI:** 95.4

**CRI R9:** 85.9

**TM30 Rf:** 93.6

**TM30 Rg:** 100.1

**CQS:** 93.2

**X:** 0.438

**Y:** 0.408

**U:** 0.249

**V:** 0.349

**Δuv:** 0.0015










| R1 | R2 | R3 | R4 | R5 | R6 | R7 | R8 | R9 | R10 | R11 | R12 | R13 | R14 | R15 |
|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|
| 96.3 | 95.9 | 93.0 | 96.6 | 94.6 | 93.4 | 98.6 | 95.2 | 85.9 | 88.2 | 95.8 | 77.2 | 96.0 | 95.2 | 95.4 |
| **Q1** | **Q2** | **Q3** | **Q4** | **Q5** | **Q6** | **Q7** | **Q8** | **Q9** | **Q10** | **Q11** | **Q12** | **Q13** | **Q14** | **Q15** |
| 94.8 | 97.5 | 88.4 | 88.6 | 92.0 | 93.0 | 92.7 | 95.4 | 95.5 | 94.3 | 94.3 | 95.4 | 96.1 | 94.6 | 94.9 |
| **C1** | **C2** | **C3** | **C4** | **C5** | **C6** | **C7** | **C8** | **C9** | **C10** | **C11** | **C12** | **C13** | **C14** | **C15** | **C16** |
| 95.5 | 96.3 | 93.9 | 94.7 | 93.4 | 96.8 | 94.6 | 97.7 | 94.5 | 88.3 | 87.8 | 91.0 | 96.2 | 93.1 | 93.7 | 90.5 |

| TM30 | | | |
|---|---|---|---|
| Hue Bin | $R_f$ | Chroma | Hue |
| 1 | 95 | -2% | 0% |
| 2 | 96 | -2% | 1% |
| 3 | 94 | -1% | 3% |
| 4 | 95 | -2% | 2% |
| 5 | 93 | -2% | 2% |
| 6 | 97 | 1% | 1% |
| 7 | 95 | -2% | 0% |
| 8 | 98 | -1% | 0% |
| 9 | 94 | -2% | 3% |
| 10 | 88 | -2% | 7% |
| 11 | 88 | 1% | 9% |
| 12 | 91 | 4% | 4% |
| 13 | 96 | 2% | 0% |
| 14 | 93 | 5% | -3% |
| 15 | 94 | 1% | -3% |
| 16 | 90 | 2% | -8% |

**NOTES:**
- CRI R values, only R1-R8 are used to calculate RA CRI values
- TM30 C values, 16 binned values out of total of 99 C values
- CQS Q values
- Data subject to change, all data has +/- 5% tolerance

© 2024 QTL. All rights reserved | 155 Hill St. Milford, CT 06460 | 203-367-8777 | sales@QTL.lighting | QTL.lighting

Specification subject to change. Rev-03-10-24

# Q-CAP LUME-SW(01)

Flexible Fixtures Color Data

## LUME-01-SW-DRY-35-1.5-ENC/TL

3636 K

**CRI:** 97.9

**CRI R9:** 97.7

**TM30 Rf:** 93.0

**TM30 Rg:** 99.4

**CQS:** 95.8

**X:** 0.399

**Y:** 0.391

**U:** 0.232

**V:** 0.340

**Δuv:** 0.0013










| R1 | R2 | R3 | R4 | R5 | R6 | R7 | R8 | R9 | R10 | R11 | R12 | R13 | R14 | R15 |
|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|
| 99.1 | 98.9 | 95.6 | 98.8 | 97.5 | 96.6 | 98.5 | 98.1 | 97.7 | 95.5 | 98.6 | 76.1 | 99.3 | 96.8 | 97.2 |

| Q1 | Q2 | Q3 | Q4 | Q5 | Q6 | Q7 | Q8 | Q9 | Q10 | Q11 | Q12 | Q13 | Q14 | Q15 |
|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|
| 93.4 | 98.5 | 91.8 | 91.2 | 94.3 | 96.6 | 98.1 | 99.2 | 98.1 | 98.0 | 98.7 | 98.6 | 98.7 | 98.9 | 96.8 |

| C1 | C2 | C3 | C4 | C5 | C6 | C7 | C8 | C9 | C10 | C11 | C12 | C13 | C14 | C15 | C16 |
|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|
| 95.2 | 97.5 | 96.6 | 93.4 | 91.9 | 96.2 | 93.1 | 95.0 | 91.7 | 87.6 | 88.1 | 92.6 | 96.1 | 93.0 | 91.5 | 90.8 |

| TM30 | | | |
|---|---|---|---|
| Hue Bin | $R_f$ | Chroma | Hue |
| 1 | 95 | -1% | 0% |
| 2 | 98 | 0% | -1% |
| 3 | 97 | 0% | 0% |
| 4 | 93 | -3% | -2% |
| 5 | 92 | -6% | 0% |
| 6 | 96 | -2% | 1% |
| 7 | 93 | -4% | 3% |
| 8 | 95 | -1% | 3% |
| 9 | 92 | -1% | 6% |
| 10 | 88 | 1% | 9% |
| 11 | 88 | 4% | 7% |
| 12 | 93 | 4% | 2% |
| 13 | 96 | 1% | -2% |
| 14 | 93 | 4% | -3% |
| 15 | 92 | 1% | -2% |
| 16 | 91 | 2% | -5% |

## LUME-01-SW-DRY-35-3.0-ENC/TL

3617 K

**CRI:** 97.9

**CRI R9:** 95.9

**TM30 Rf:** 93.3

**TM30 Rg:** 99.5

**CQS:** 95.8

**X:** 0.400

**Y:** 0.390

**U:** 0.233

**V:** 0.340

**Δuv:** 0.0008










| R1 | R2 | R3 | R4 | R5 | R6 | R7 | R8 | R9 | R10 | R11 | R12 | R13 | R14 | R15 |
|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|
| 99.1 | 98.9 | 95.7 | 98.7 | 97.4 | 96.6 | 98.7 | 98.0 | 95.9 | 95.2 | 98.4 | 77.1 | 99.4 | 96.8 | 97.4 |

| Q1 | Q2 | Q3 | Q4 | Q5 | Q6 | Q7 | Q8 | Q9 | Q10 | Q11 | Q12 | Q13 | Q14 | Q15 |
|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|
| 93.9 | 98.6 | 91.5 | 91.0 | 94.2 | 96.6 | 97.6 | 98.8 | 98.1 | 98.2 | 98.6 | 99.2 | 99.3 | 98.7 | 97.0 |

| C1 | C2 | C3 | C4 | C5 | C6 | C7 | C8 | C9 | C10 | C11 | C12 | C13 | C14 | C15 | C16 |
|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|
| 95.3 | 97.6 | 96.5 | 93.8 | 92.5 | 96.5 | 93.9 | 95.5 | 92.3 | 88.1 | 88.4 | 92.7 | 96.2 | 93.1 | 91.9 | 91.2 |

| TM30 | | | |
|---|---|---|---|
| Hue Bin | $R_f$ | Chroma | Hue |
| 1 | 95 | -1% | 0% |
| 2 | 98 | 0% | 0% |
| 3 | 97 | 0% | 0% |
| 4 | 94 | -3% | -1% |
| 5 | 92 | -5% | 0% |
| 6 | 97 | -1% | 1% |
| 7 | 94 | -3% | 3% |
| 8 | 95 | -1% | 3% |
| 9 | 92 | -1% | 5% |
| 10 | 88 | 0% | 8% |
| 11 | 88 | 4% | 7% |
| 12 | 93 | 4% | 2% |
| 13 | 96 | 1% | -2% |
| 14 | 93 | 4% | -3% |
| 15 | 92 | 1% | -2% |
| 16 | 91 | 1% | -4% |

## LUME-01-SW-DRY-35-5.0-ENC/TL

3545 K

**CRI:** 98.2

**CRI R9:** 98.8

**TM30 Rf:** 93.5

**TM30 Rg:** 99.9

**CQS:** 96.0

**X:** 0.403

**Y:** 0.388

**U:** 0.235

**V:** 0.340

**Δuv:** -0.0005










| R1 | R2 | R3 | R4 | R5 | R6 | R7 | R8 | R9 | R10 | R11 | R12 | R13 | R14 | R15 |
|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|
| 98.4 | 99.8 | 96.3 | 99.3 | 98.1 | 97.1 | 98.5 | 98.2 | 98.8 | 97.8 | 98.3 | 78.9 | 98.7 | 97.0 | 97.2 |

| Q1 | Q2 | Q3 | Q4 | Q5 | Q6 | Q7 | Q8 | Q9 | Q10 | Q11 | Q12 | Q13 | Q14 | Q15 |
|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|
| 94.0 | 98.6 | 92.0 | 91.5 | 94.6 | 97.3 | 97.7 | 98.9 | 98.1 | 98.5 | 98.9 | 99.8 | 99.4 | 98.2 | 96.8 |

| C1 | C2 | C3 | C4 | C5 | C6 | C7 | C8 | C9 | C10 | C11 | C12 | C13 | C14 | C15 | C16 |
|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|
| 95.4 | 97.5 | 96.8 | 94.0 | 92.6 | 97.2 | 93.5 | 95.5 | 92.4 | 88.6 | 89.0 | 93.0 | 96.1 | 93.4 | 92.1 | 91.6 |

| TM30 | | | |
|---|---|---|---|
| Hue Bin | $R_f$ | Chroma | Hue |
| 1 | 95 | 0% | 1% |
| 2 | 98 | 0% | -1% |
| 3 | 97 | 0% | 0% |
| 4 | 94 | -3% | -1% |
| 5 | 93 | -5% | 0% |
| 6 | 97 | -1% | 1% |
| 7 | 93 | -3% | 3% |
| 8 | 96 | -1% | 3% |
| 9 | 92 | 0% | 5% |
| 10 | 89 | 1% | 8% |
| 11 | 89 | 4% | 7% |
| 12 | 93 | 4% | 1% |
| 13 | 96 | 1% | -2% |
| 14 | 93 | 4% | -3% |
| 15 | 92 | 1% | -2% |
| 16 | 92 | 1% | -4% |

**NOTES:**
- CRI R values, only R1-R8 are used to calculate RA CRI values
- TM30 C values, 16 binned values out of total of 99 C values
- CQS Q values
- Data subject to change, all data has +/- 5% tolerance

© 2024 QTL. All rights reserved | 155 Hill St. Milford, CT 06460 | 203-367-8777 | sales@QTL.lighting | QTL.lighting

Specification subject to change. Rev-03-10-24

# Q-CAP LUME-SW(01)

Flexible Fixtures Color Data

## LUME-01-SW-DRY-40-1.5-ENC/TL

3778 K

**CRI:** 97.3

**CRI R9:** 95.5

**TM30 Rf:** 91.6

**TM30 Rg:** 98.4

**CQS:** 94.8

**X:** 0.391

**Y:** 0.384

**U:** 0.229

**V:** 0.338

**Δuv:** 0.0005










| R1 | R2 | R3 | R4 | R5 | R6 | R7 | R8 | R9 | R10 | R11 | R12 | R13 | R14 | R15 |
|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|
| 98.6 | 99.6 | 97.4 | 96.5 | 96.4 | 96.5 | 96.9 | 96.4 | 95.5 | 96.8 | 97.8 | 73.7 | 99.3 | 97.8 | 96.4 |
| **Q1** | **Q2** | **Q3** | **Q4** | **Q5** | **Q6** | **Q7** | **Q8** | **Q9** | **Q10** | **Q11** | **Q12** | **Q13** | **Q14** | **Q15** |
| 91.5 | 97.6 | 91.2 | 89.2 | 91.7 | 94.0 | 98.0 | 98.4 | 98.6 | 98.4 | 98.6 | 99.4 | 99.8 | 98.2 | 95.8 |
| **C1** | **C2** | **C3** | **C4** | **C5** | **C6** | **C7** | **C8** | **C9** | **C10** | **C11** | **C12** | **C13** | **C14** | **C15** | **C16** |
| 93.8 | 96.7 | 96.3 | 92.2 | 90.5 | 95.1 | 92.1 | 91.0 | 87.7 | 86.6 | 87.0 | 92.2 | 95.2 | 92.0 | 90.4 | 89.8 |

| TM30 | | | |
|---|---|---|---|
| Hue Bin | $R_f$ | Chroma | Hue |
| 1 | 94 | -1% | 1% |
| 2 | 97 | 0% | 0% |
| 3 | 96 | -1% | 0% |
| 4 | 92 | -4% | -2% |
| 5 | 91 | -7% | -1% |
| 6 | 95 | -3% | 1% |
| 7 | 92 | -4% | 3% |
| 8 | 91 | -2% | 5% |
| 9 | 88 | -1% | 9% |
| 10 | 87 | 0% | 9% |
| 11 | 87 | 5% | 8% |
| 12 | 92 | 4% | 1% |
| 13 | 95 | 1% | -3% |
| 14 | 92 | 4% | -4% |
| 15 | 90 | 0% | -3% |
| 16 | 90 | 1% | -5% |

## LUME-01-SW-DRY-40-3.0-ENC/TL

3762 K

**CRI:** 97.1

**CRI R9:** 94.0

**TM30 Rf:** 91.3

**TM30 Rg:** 98.2

**CQS:** 94.5

**X:** 0.392

**Y:** 0.384

**U:** 0.230

**V:** 0.338

**Δuv:** 0.0002










| R1 | R2 | R3 | R4 | R5 | R6 | R7 | R8 | R9 | R10 | R11 | R12 | R13 | R14 | R15 |
|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|
| 98.5 | 99.8 | 97.6 | 96.0 | 96.2 | 96.4 | 96.4 | 95.8 | 94.0 | 97.0 | 97.0 | 73.8 | 99.3 | 97.9 | 96.4 |
| **Q1** | **Q2** | **Q3** | **Q4** | **Q5** | **Q6** | **Q7** | **Q8** | **Q9** | **Q10** | **Q11** | **Q12** | **Q13** | **Q14** | **Q15** |
| 91.2 | 97.4 | 91.1 | 88.6 | 91.0 | 93.2 | 97.7 | 98.1 | 98.7 | 98.5 | 98.2 | 99.1 | 99.5 | 97.8 | 95.5 |
| **C1** | **C2** | **C3** | **C4** | **C5** | **C6** | **C7** | **C8** | **C9** | **C10** | **C11** | **C12** | **C13** | **C14** | **C15** | **C16** |
| 93.4 | 96.4 | 96.2 | 91.9 | 90.3 | 94.8 | 90.3 | 92.5 | 88.8 | 84.5 | 86.8 | 92.2 | 94.9 | 91.8 | 90.1 | 89.6 |

| TM30 | | | |
|---|---|---|---|
| Hue Bin | $R_f$ | Chroma | Hue |
| 1 | 93 | -1% | 1% |
| 2 | 96 | 0% | 0% |
| 3 | 96 | -1% | 0% |
| 4 | 92 | -4% | -2% |
| 5 | 90 | -7% | -1% |
| 6 | 95 | -3% | 1% |
| 7 | 90 | -5% | 4% |
| 8 | 92 | -2% | 4% |
| 9 | 89 | -1% | 8% |
| 10 | 84 | 1% | 11% |
| 11 | 87 | 5% | 8% |
| 12 | 92 | 4% | 1% |
| 13 | 95 | 0% | -3% |
| 14 | 92 | 4% | -4% |
| 15 | 90 | 0% | -3% |
| 16 | 90 | 1% | -5% |

## LUME-01-SW-DRY-40-5.0-ENC/TL

3781 K

**CRI:** 97.3

**CRI R9:** 96.0

**TM30 Rf:** 91.7

**TM30 Rg:** 98.2

**CQS:** 94.9

**X:** 0.391

**Y:** 0.383

**U:** 0.229

**V:** 0.337

**Δuv:** 0.0001










| R1 | R2 | R3 | R4 | R5 | R6 | R7 | R8 | R9 | R10 | R11 | R12 | R13 | R14 | R15 |
|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|
| 98.6 | 99.5 | 98.0 | 96.4 | 96.6 | 96.8 | 96.2 | 96.2 | 96.0 | 98.5 | 98.1 | 75.7 | 99.1 | 98.1 | 96.5 |
| **Q1** | **Q2** | **Q3** | **Q4** | **Q5** | **Q6** | **Q7** | **Q8** | **Q9** | **Q10** | **Q11** | **Q12** | **Q13** | **Q14** | **Q15** |
| 91.3 | 97.1 | 92.3 | 89.8 | 91.6 | 93.7 | 98.4 | 98.6 | 98.8 | 98.8 | 98.9 | 99.8 | 99.9 | 97.9 | 95.6 |
| **C1** | **C2** | **C3** | **C4** | **C5** | **C6** | **C7** | **C8** | **C9** | **C10** | **C11** | **C12** | **C13** | **C14** | **C15** | **C16** |
| 93.8 | 96.6 | 96.5 | 92.2 | 90.5 | 94.8 | 91.8 | 90.6 | 87.6 | 86.8 | 87.9 | 92.8 | 94.8 | 92.4 | 90.6 | 90.2 |

| TM30 | | | |
|---|---|---|---|
| Hue Bin | $R_f$ | Chroma | Hue |
| 1 | 94 | -1% | 1% |
| 2 | 97 | 0% | 0% |
| 3 | 97 | -1% | -1% |
| 4 | 92 | -4% | -3% |
| 5 | 90 | -7% | -1% |
| 6 | 95 | -3% | 1% |
| 7 | 92 | -4% | 3% |
| 8 | 91 | -2% | 5% |
| 9 | 88 | -1% | 9% |
| 10 | 87 | 1% | 8% |
| 11 | 88 | 5% | 7% |
| 12 | 93 | 4% | 0% |
| 13 | 95 | 0% | -3% |
| 14 | 92 | 3% | -4% |
| 15 | 91 | 0% | -2% |
| 16 | 90 | 1% | -4% |

**NOTES:**
- CRI R values, only R1-R8 are used to calculate RA CRI values
- TM30 C values, 16 binned values out of total of 99 C values
- CQS Q values
- Data subject to change, all data has +/- 5% tolerance

© 2024 QTL. All rights reserved | 155 Hill St. Milford, CT 06460 | 203-367-8777 | sales@QTL.lighting | QTL.lighting

Specification subject to change. Rev-03-10-24

# Q-CAP LUME-SW-HE(01)

Flexible Fixtures Color Data

## LUME-01-SW-DRY-24-1.5HE-ENC/TL

2430 K

**CRI:** 93.0

**CRI R9:** 67.9

**TM30 Rf:** 92.3

**TM30 Rg:** 100.4

**CQS:** 88.7

**X:** 0.487

**Y:** 0.420

**U:** 0.276

**V:** 0.357

**Δuv:** 0.0019










| R1 | R2 | R3 | R4 | R5 | R6 | R7 | R8 | R9 | R10 | R11 | R12 | R13 | R14 | R15 |
|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|
| 93.8 | 94.7 | 92.8 | 94.9 | 92.3 | 93.4 | 95.3 | 86.5 | 67.9 | 85.4 | 95.3 | 78.0 | 93.9 | 94.5 | 90.2 |
| **Q1** | **Q2** | **Q3** | **Q4** | **Q5** | **Q6** | **Q7** | **Q8** | **Q9** | **Q10** | **Q11** | **Q12** | **Q13** | **Q14** | **Q15** |
| 87.9 | 93.5 | 86.5 | 87.2 | 88.8 | 87.4 | 87.5 | 91.3 | 93.2 | 90.8 | 88.2 | 89.7 | 90.9 | 86.2 | 87.0 |
| **C1** | **C2** | **C3** | **C4** | **C5** | **C6** | **C7** | **C8** | **C9** | **C10** | **C11** | **C12** | **C13** | **C14** | **C15** | **C16** |
| 92.8 | 93.3 | 89.7 | 93.4 | 94.1 | 94.1 | 94.4 | 96.4 | 95.4 | 91.2 | 89.1 | 89.8 | 92.5 | 88.3 | 94.1 | 88.4 |

| TM30 | | | |
|---|---|---|---|
| Hue Bin | $R_f$ | Chroma | Hue |
| 1 | 93 | -4% | -1% |
| 2 | 93 | -4% | 2% |
| 3 | 90 | -2% | 5% |
| 4 | 93 | -1% | 3% |
| 5 | 94 | 1% | 4% |
| 6 | 94 | 4% | 2% |
| 7 | 94 | 1% | -3% |
| 8 | 96 | 0% | -2% |
| 9 | 95 | -2% | 0% |
| 10 | 91 | -3% | 4% |
| 11 | 89 | 1% | 8% |
| 12 | 90 | 3% | 4% |
| 13 | 93 | 4% | -5% |
| 14 | 88 | 4% | -7% |
| 15 | 94 | 1% | -4% |
| 16 | 88 | -1% | -9% |

## LUME-01-SW-DRY-24-3.0HE-ENC/TL

2442 K

**CRI:** 93.2

**CRI R9:** 67.9

**TM30 Rf:** 92.4

**TM30 Rg:** 100.9

**CQS:** 89.0

**X:** 0.485

**Y:** 0.418

**U:** 0.275

**V:** 0.356

**Δuv:** 0.0012










| R1 | R2 | R3 | R4 | R5 | R6 | R7 | R8 | R9 | R10 | R11 | R12 | R13 | R14 | R15 |
|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|
| 94.1 | 95.1 | 93.7 | 95.0 | 92.8 | 94.2 | 94.8 | 86.3 | 67.9 | 86.6 | 95.6 | 80.8 | 94.3 | 95.1 | 90.4 |
| **Q1** | **Q2** | **Q3** | **Q4** | **Q5** | **Q6** | **Q7** | **Q8** | **Q9** | **Q10** | **Q11** | **Q12** | **Q13** | **Q14** | **Q15** |
| 87.4 | 93.6 | 87.0 | 88.0 | 89.1 | 87.2 | 86.9 | 90.6 | 93.9 | 91.2 | 90.4 | 91.4 | 91.8 | 86.7 | 86.8 |
| **C1** | **C2** | **C3** | **C4** | **C5** | **C6** | **C7** | **C8** | **C9** | **C10** | **C11** | **C12** | **C13** | **C14** | **C15** | **C16** |
| 92.9 | 93.2 | 89.1 | 93.2 | 94.2 | 93.2 | 93.2 | 95.3 | 95.5 | 92.4 | 90.5 | 90.1 | 92.4 | 88.5 | 93.7 | 89.2 |

| TM30 | | | |
|---|---|---|---|
| Hue Bin | $R_f$ | Chroma | Hue |
| 1 | 93 | -4% | -1% |
| 2 | 93 | -4% | 2% |
| 3 | 89 | -1% | 5% |
| 4 | 93 | 0% | 4% |
| 5 | 94 | 3% | 4% |
| 6 | 93 | 5% | 1% |
| 7 | 93 | 2% | -4% |
| 8 | 95 | 0% | -3% |
| 9 | 96 | -2% | -1% |
| 10 | 92 | -3% | 3% |
| 11 | 90 | 0% | 7% |
| 12 | 90 | 2% | 4% |
| 13 | 92 | 4% | -5% |
| 14 | 88 | 4% | -7% |
| 15 | 94 | 1% | -4% |
| 16 | 89 | -2% | -8% |

## LUME-01-SW-DRY-24-6.0HE-ENC/TL

2398 K

**CRI:** 93.0

**CRI R9:** 66.8

**TM30 Rf:** 91.5

**TM30 Rg:** 101.7

**CQS:** 87.9

**X:** 0.487

**Y:** 0.415

**U:** 0.278

**V:** 0.355

**Δuv:** 0.0003










| R1 | R2 | R3 | R4 | R5 | R6 | R7 | R8 | R9 | R10 | R11 | R12 | R13 | R14 | R15 |
|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|
| 93.9 | 95.5 | 94.2 | 94.1 | 92.6 | 94.5 | 93.9 | 85.2 | 66.8 | 87.2 | 94.5 | 81.5 | 94.3 | 95.3 | 90.4 |
| **Q1** | **Q2** | **Q3** | **Q4** | **Q5** | **Q6** | **Q7** | **Q8** | **Q9** | **Q10** | **Q11** | **Q12** | **Q13** | **Q14** | **Q15** |
| 86.3 | 93.0 | 85.6 | 86.3 | 88.4 | 86.2 | 84.3 | 88.1 | 93.9 | 90.0 | 90.5 | 90.9 | 91.1 | 86.4 | 86.0 |
| **C1** | **C2** | **C3** | **C4** | **C5** | **C6** | **C7** | **C8** | **C9** | **C10** | **C11** | **C12** | **C13** | **C14** | **C15** | **C16** |
| 92.3 | 92.7 | 87.2 | 92.1 | 93.4 | 92.2 | 92.0 | 94.2 | 95.3 | 91.6 | 89.3 | 89.2 | 91.5 | 87.0 | 92.9 | 88.0 |

| TM30 | | | |
|---|---|---|---|
| Hue Bin | $R_f$ | Chroma | Hue |
| 1 | 92 | -4% | -1% |
| 2 | 93 | -4% | 3% |
| 3 | 87 | -1% | 6% |
| 4 | 92 | 1% | 4% |
| 5 | 93 | 4% | 5% |
| 6 | 92 | 6% | 1% |
| 7 | 92 | 2% | -4% |
| 8 | 94 | 0% | -4% |
| 9 | 95 | -2% | -1% |
| 10 | 92 | -3% | 4% |
| 11 | 89 | 1% | 8% |
| 12 | 89 | 3% | 4% |
| 13 | 92 | 5% | -5% |
| 14 | 87 | 5% | -8% |
| 15 | 93 | 1% | -5% |
| 16 | 88 | -2% | -9% |

**NOTES:**
- CRI R values, only R1-R8 are used to calculate RA CRI values
- TM30 C values, 16 binned values out of total of 99 C values
- CQS Q values
- Data subject to change, all data has +/- 5% tolerance

© 2024 QTL. All rights reserved | 155 Hill St. Milford, CT 06460 | 203-367-8777 | sales@QTL.lighting | QTL.lighting

Specification subject to change. Rev-03-10-24

# Q-CAP LUME-SW-HE(01)

Flexible Fixtures Color Data

## LUME-01-SW-DRY-27-1.5HE-ENC/TL

2751 K

**CRI:** 97.0

**CRI R9:** 92.6

**TM30 Rf:** 94.2

**TM30 Rg:** 101.3

**CQS:** 93.6

**X:** 0.457

**Y:** 0.412

**U:** 0.260

**V:** 0.352

**Δuv:** 0.0009










| R1 | R2 | R3 | R4 | R5 | R6 | R7 | R8 | R9 | R10 | R11 | R12 | R13 | R14 | R15 |
|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|
| 98.5 | 97.0 | 92.9 | 98.3 | 97.1 | 95.3 | 98.8 | 98.0 | 92.6 | 91.1 | 97.3 | 79.7 | 98.1 | 95.0 | 97.7 |
| **Q1** | **Q2** | **Q3** | **Q4** | **Q5** | **Q6** | **Q7** | **Q8** | **Q9** | **Q10** | **Q11** | **Q12** | **Q13** | **Q14** | **Q15** |
| 95.2 | 97.0 | 88.8 | 90.1 | 93.8 | 93.5 | 91.6 | 95.2 | 95.1 | 94.5 | 95.0 | 96.0 | 96.7 | 96.0 | 96.0 |
| **C1** | **C2** | **C3** | **C4** | **C5** | **C6** | **C7** | **C8** | **C9** | **C10** | **C11** | **C12** | **C13** | **C14** | **C15** | **C16** |
| 96.7 | 97.5 | 94.8 | 94.3 | 94.5 | 96.1 | 94.2 | 98.4 | 96.3 | 91.3 | 88.9 | 91.1 | 96.2 | 93.0 | 95.4 | 89.8 |

| TM30 | | | |
|---|---|---|---|
| Hue Bin | $R_f$ | Chroma | Hue |
| 1 | 97 | -1% | 0% |
| 2 | 98 | -1% | 0% |
| 3 | 95 | 0% | 2% |
| 4 | 94 | -2% | 1% |
| 5 | 95 | 0% | 3% |
| 6 | 96 | 2% | 1% |
| 7 | 94 | -1% | 0% |
| 8 | 98 | 0% | -1% |
| 9 | 96 | -1% | 2% |
| 10 | 91 | -1% | 6% |
| 11 | 89 | 2% | 8% |
| 12 | 91 | 4% | 3% |
| 13 | 96 | 2% | 0% |
| 14 | 93 | 5% | -3% |
| 15 | 95 | 0% | -1% |
| 16 | 90 | 3% | -8% |

## LUME-01-SW-DRY-27-3.0HE-ENC/TL

2730 K

**CRI:** 97.2

**CRI R9:** 93.0

**TM30 Rf:** 94.6

**TM30 Rg:** 101.7

**CQS:** 93.5

**X:** 0.458

**Y:** 0.410

**U:** 0.261

**V:** 0.351

**Δuv:** 0.0002










| R1 | R2 | R3 | R4 | R5 | R6 | R7 | R8 | R9 | R10 | R11 | R12 | R13 | R14 | R15 |
|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|
| 98.8 | 97.5 | 93.3 | 98.1 | 97.5 | 96.0 | 98.7 | 98.0 | 93.0 | 91.9 | 97.2 | 82.2 | 98.5 | 95.1 | 98.1 |
| **Q1** | **Q2** | **Q3** | **Q4** | **Q5** | **Q6** | **Q7** | **Q8** | **Q9** | **Q10** | **Q11** | **Q12** | **Q13** | **Q14** | **Q15** |
| 95.6 | 96.9 | 89.0 | 90.3 | 93.9 | 93.2 | 90.7 | 94.4 | 95.2 | 94.1 | 95.2 | 96.4 | 97.1 | 96.0 | 95.9 |
| **C1** | **C2** | **C3** | **C4** | **C5** | **C6** | **C7** | **C8** | **C9** | **C10** | **C11** | **C12** | **C13** | **C14** | **C15** | **C16** |
| 97.1 | 97.6 | 94.5 | 94.8 | 94.7 | 95.3 | 95.5 | 97.6 | 97.0 | 92.5 | 90.0 | 91.8 | 96.1 | 93.7 | 95.9 | 91.2 |

| TM30 | | | |
|---|---|---|---|
| Hue Bin | $R_f$ | Chroma | Hue |
| 1 | 97 | -1% | 0% |
| 2 | 98 | -1% | 0% |
| 3 | 94 | 0% | 2% |
| 4 | 95 | -1% | 1% |
| 5 | 95 | 1% | 3% |
| 6 | 95 | 3% | 1% |
| 7 | 95 | 1% | -1% |
| 8 | 98 | 0% | -2% |
| 9 | 97 | -1% | 1% |
| 10 | 92 | -1% | 5% |
| 11 | 90 | 1% | 7% |
| 12 | 92 | 4% | 3% |
| 13 | 96 | 3% | -1% |
| 14 | 94 | 5% | -2% |
| 15 | 96 | 0% | -1% |
| 16 | 91 | 2% | -7% |

## LUME-01-SW-DRY-27-6.0HE-ENC/TL

2721 K

**CRI:** 97.0

**CRI R9:** 91.4

**TM30 Rf:** 94.5

**TM30 Rg:** 101.6

**CQS:** 93.4

**X:** 0.458

**Y:** 0.410

**U:** 0.262

**V:** 0.351

**Δuv:** 0.0001










| R1 | R2 | R3 | R4 | R5 | R6 | R7 | R8 | R9 | R10 | R11 | R12 | R13 | R14 | R15 |
|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|
| 98.5 | 97.4 | 93.7 | 97.9 | 97.3 | 96.0 | 98.5 | 97.1 | 91.4 | 91.9 | 97.3 | 82.8 | 98.2 | 95.3 | 97.7 |
| **Q1** | **Q2** | **Q3** | **Q4** | **Q5** | **Q6** | **Q7** | **Q8** | **Q9** | **Q10** | **Q11** | **Q12** | **Q13** | **Q14** | **Q15** |
| 95.3 | 96.8 | 89.1 | 90.2 | 93.7 | 93.1 | 90.7 | 94.2 | 95.4 | 94.0 | 94.9 | 96.1 | 96.8 | 95.6 | 95.4 |
| **C1** | **C2** | **C3** | **C4** | **C5** | **C6** | **C7** | **C8** | **C9** | **C10** | **C11** | **C12** | **C13** | **C14** | **C15** | **C16** |
| 96.7 | 97.3 | 94.3 | 94.7 | 94.8 | 95.4 | 95.6 | 97.8 | 96.8 | 92.3 | 89.9 | 91.6 | 95.8 | 93.2 | 95.9 | 90.6 |

| TM30 | | | |
|---|---|---|---|
| Hue Bin | $R_f$ | Chroma | Hue |
| 1 | 97 | -1% | 0% |
| 2 | 97 | -1% | 1% |
| 3 | 94 | 0% | 3% |
| 4 | 95 | -1% | 1% |
| 5 | 95 | 1% | 3% |
| 6 | 95 | 3% | 1% |
| 7 | 96 | 0% | -1% |
| 8 | 98 | 0% | -1% |
| 9 | 97 | -1% | 1% |
| 10 | 92 | -1% | 5% |
| 11 | 90 | 1% | 8% |
| 12 | 92 | 4% | 3% |
| 13 | 96 | 3% | -1% |
| 14 | 93 | 5% | -3% |
| 15 | 96 | 0% | -1% |
| 16 | 91 | 2% | -7% |

**NOTES:**
- CRI R values, only R1-R8 are used to calculate RA CRI values
- TM30 C values, 16 binned values out of total of 99 C values
- CQS Q values
- Data subject to change, all data has +/- 5% tolerance

© 2024 QTL. All rights reserved | 155 Hill St. Milford, CT 06460 | 203-367-8777 | sales@QTL.lighting | QTL.lighting

Specification subject to change. Rev-03-10-24

# Q-CAP LUME-SW-HE(01)

Flexible Fixtures Color Data

## LUME-01-SW-DRY-30-1.5HE-ENC/TL

3089 K

**CRI:** 94.8

**CRI R9:** 86.5

**TM30 Rf:** 93.1

**TM30 Rg:** 100.4

**CQS:** 92.9

**X:** 0.435

**Y:** 0.410

**U:** 0.247

**V:** 0.349

**Δuv:** 0.0026










| R1 | R2 | R3 | R4 | R5 | R6 | R7 | R8 | R9 | R10 | R11 | R12 | R13 | R14 | R15 |
|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|
| 95.7 | 94.7 | 91.8 | 96.5 | 93.9 | 91.8 | 98.3 | 95.9 | 86.5 | 86.1 | 95.7 | 73.1 | 95.1 | 94.6 | 94.8 |
| **Q1** | **Q2** | **Q3** | **Q4** | **Q5** | **Q6** | **Q7** | **Q8** | **Q9** | **Q10** | **Q11** | **Q12** | **Q13** | **Q14** | **Q15** |
| 95.1 | 97.7 | 87.4 | 88.2 | 91.9 | 92.5 | 92.4 | 95.8 | 95.1 | 94.1 | 93.6 | 94.7 | 95.7 | 94.7 | 95.3 |
| **C1** | **C2** | **C3** | **C4** | **C5** | **C6** | **C7** | **C8** | **C9** | **C10** | **C11** | **C12** | **C13** | **C14** | **C15** | **C16** |
| 95.4 | 96.2 | 93.5 | 94.3 | 92.7 | 96.4 | 94.2 | 97.7 | 94.2 | 87.6 | 86.2 | 90.6 | 96.0 | 92.5 | 93.1 | 89.2 |

| TM30 | | | |
|---|---|---|---|
| Hue Bin | $R_f$ | Chroma | Hue |
| 1 | 95 | -2% | 0% |
| 2 | 96 | -2% | 0% |
| 3 | 94 | -1% | 3% |
| 4 | 94 | -2% | 2% |
| 5 | 93 | -3% | 2% |
| 6 | 96 | 2% | 1% |
| 7 | 94 | -2% | 0% |
| 8 | 98 | -1% | -1% |
| 9 | 94 | -2% | 3% |
| 10 | 88 | -2% | 7% |
| 11 | 86 | 1% | 10% |
| 12 | 91 | 5% | 5% |
| 13 | 96 | 3% | 1% |
| 14 | 93 | 6% | -2% |
| 15 | 93 | 1% | -3% |
| 16 | 89 | 3% | -9% |

## LUME-01-SW-DRY-30-3.0HE-ENC/TL

3061 K

**CRI:** 94.9

**CRI R9:** 86.1

**TM30 Rf:** 93.1

**TM30 Rg:** 100.4

**CQS:** 92.9

**X:** 0.436

**Y:** 0.410

**U:** 0.248

**V:** 0.349

**Δuv:** 0.0023










| R1 | R2 | R3 | R4 | R5 | R6 | R7 | R8 | R9 | R10 | R11 | R12 | R13 | R14 | R15 |
|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|
| 95.8 | 94.9 | 92.0 | 96.5 | 94.0 | 92.1 | 98.4 | 95.6 | 86.1 | 86.4 | 95.8 | 73.5 | 95.3 | 94.7 | 94.9 |
| **Q1** | **Q2** | **Q3** | **Q4** | **Q5** | **Q6** | **Q7** | **Q8** | **Q9** | **Q10** | **Q11** | **Q12** | **Q13** | **Q14** | **Q15** |
| 95.0 | 97.7 | 87.4 | 88.1 | 91.9 | 92.5 | 92.2 | 95.6 | 95.2 | 94.1 | 93.8 | 94.8 | 95.8 | 94.6 | 95.1 |
| **C1** | **C2** | **C3** | **C4** | **C5** | **C6** | **C7** | **C8** | **C9** | **C10** | **C11** | **C12** | **C13** | **C14** | **C15** | **C16** |
| 95.4 | 96.1 | 93.4 | 94.4 | 92.8 | 96.4 | 94.2 | 97.7 | 94.4 | 87.7 | 86.6 | 89.8 | 96.0 | 92.6 | 93.2 | 89.5 |

| TM30 | | | |
|---|---|---|---|
| Hue Bin | $R_f$ | Chroma | Hue |
| 1 | 95 | -2% | 0% |
| 2 | 96 | -2% | 0% |
| 3 | 93 | -1% | 3% |
| 4 | 94 | -2% | 2% |
| 5 | 93 | -2% | 3% |
| 6 | 96 | 2% | 1% |
| 7 | 94 | -1% | 0% |
| 8 | 98 | -1% | -1% |
| 9 | 94 | -2% | 3% |
| 10 | 88 | -2% | 7% |
| 11 | 87 | 1% | 10% |
| 12 | 90 | 4% | 5% |
| 13 | 96 | 3% | 0% |
| 14 | 93 | 6% | -2% |
| 15 | 93 | 1% | -3% |
| 16 | 89 | 2% | -8% |

## LUME-01-SW-DRY-30-6.0HE-ENC/TL

3008 K

**CRI:** 95.2

**CRI R9:** 87.0

**TM30 Rf:** 93.2

**TM30 Rg:** 100.9

**CQS:** 92.8

**X:** 0.439

**Y:** 0.408

**U:** 0.250

**V:** 0.349

**Δuv:** 0.0014










| R1 | R2 | R3 | R4 | R5 | R6 | R7 | R8 | R9 | R10 | R11 | R12 | R13 | R14 | R15 |
|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|
| 96.2 | 95.3 | 92.3 | 96.5 | 94.5 | 92.6 | 98.2 | 95.8 | 87.0 | 87.3 | 95.8 | 75.3 | 95.7 | 94.8 | 95.5 |
| **Q1** | **Q2** | **Q3** | **Q4** | **Q5** | **Q6** | **Q7** | **Q8** | **Q9** | **Q10** | **Q11** | **Q12** | **Q13** | **Q14** | **Q15** |
| 95.3 | 97.6 | 87.2 | 88.1 | 91.9 | 92.4 | 91.3 | 94.9 | 95.2 | 93.7 | 94.1 | 95.2 | 96.1 | 94.8 | 95.1 |
| **C1** | **C2** | **C3** | **C4** | **C5** | **C6** | **C7** | **C8** | **C9** | **C10** | **C11** | **C12** | **C13** | **C14** | **C15** | **C16** |
| 95.6 | 96.2 | 93.0 | 94.5 | 93.0 | 96.0 | 94.4 | 97.6 | 95.0 | 88.9 | 86.8 | 89.7 | 95.8 | 92.5 | 93.4 | 89.6 |

| TM30 | | | |
|---|---|---|---|
| Hue Bin | $R_f$ | Chroma | Hue |
| 1 | 96 | -2% | 0% |
| 2 | 96 | -2% | 1% |
| 3 | 93 | -1% | 3% |
| 4 | 94 | -1% | 2% |
| 5 | 93 | -2% | 3% |
| 6 | 96 | 2% | 0% |
| 7 | 94 | -1% | 0% |
| 8 | 98 | -1% | -1% |
| 9 | 95 | -2% | 2% |
| 10 | 89 | -2% | 7% |
| 11 | 87 | 1% | 10% |
| 12 | 90 | 4% | 5% |
| 13 | 96 | 3% | 0% |
| 14 | 92 | 6% | -2% |
| 15 | 93 | 2% | -3% |
| 16 | 90 | 2% | -8% |

**NOTES:**
- CRI R values, only R1-R8 are used to calculate RA CRI values
- TM30 C values, 16 binned values out of total of 99 C values
- CQS Q values
- Data subject to change, all data has +/- 5% tolerance

© 2024 QTL. All rights reserved | 155 Hill St. Milford, CT 06460 | 203-367-8777 | sales@QTL.lighting | QTL.lighting

Specification subject to change. Rev-03-10-24

# Q-CAP LUME-SW-HE(01)

Flexible Fixtures Color Data

## LUME-01-SW-DRY-35-1.5HE-ENC/TL

3603 K

**CRI:** 96.9

**CRI R9:** 95.4

**TM30 Rf:** 91.2

**TM30 Rg:** 97.3

**CQS:** 94.4

**X:** 0.404

**Y:** 0.400

**U:** 0.231

**V:** 0.343

**Δuv:** 0.0041










| R1 | R2 | R3 | R4 | R5 | R6 | R7 | R8 | R9 | R10 | R11 | R12 | R13 | R14 | R15 |
|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|
| 98.7 | 98.2 | 96.3 | 96.1 | 96.2 | 96.9 | 96.4 | 96.3 | 95.4 | 94.7 | 98.3 | 73.8 | 98.3 | 97.2 | 95.7 |
| **Q1** | **Q2** | **Q3** | **Q4** | **Q5** | **Q6** | **Q7** | **Q8** | **Q9** | **Q10** | **Q11** | **Q12** | **Q13** | **Q14** | **Q15** |
| 89.9 | 95.7 | 94.0 | 91.9 | 92.7 | 93.5 | 97.3 | 97.5 | 94.7 | 92.7 | 95.7 | 95.9 | 97.0 | 99.2 | 95.5 |
| **C1** | **C2** | **C3** | **C4** | **C5** | **C6** | **C7** | **C8** | **C9** | **C10** | **C11** | **C12** | **C13** | **C14** | **C15** | **C16** |
| 94.0 | 96.4 | 95.4 | 90.9 | 88.8 | 93.1 | 89.0 | 91.9 | 88.9 | 85.3 | 88.4 | 93.2 | 95.0 | 92.6 | 90.3 | 90.1 |

| TM30 | | | |
|---|---|---|---|
| Hue Bin | $R_f$ | Chroma | Hue |
| 1 | 94 | -1% | 1% |
| 2 | 96 | 0% | -1% |
| 3 | 95 | -1% | -2% |
| 4 | 91 | -5% | -3% |
| 5 | 89 | -9% | -1% |
| 6 | 93 | -5% | 2% |
| 7 | 89 | -6% | 5% |
| 8 | 92 | -2% | 5% |
| 9 | 89 | -1% | 8% |
| 10 | 85 | 1% | 10% |
| 11 | 88 | 4% | 7% |
| 12 | 93 | 3% | 0% |
| 13 | 95 | -1% | -3% |
| 14 | 93 | 3% | -4% |
| 15 | 90 | 0% | -2% |
| 16 | 90 | 1% | -4% |

## LUME-01-SW-DRY-35-3.0HE-ENC/TL

3587 K

**CRI:** 96.9

**CRI R9:** 94.9

**TM30 Rf:** 91.5

**TM30 Rg:** 97.3

**CQS:** 94.5

**X:** 0.405

**Y:** 0.400

**U:** 0.232

**V:** 0.343

**Δuv:** 0.0041










| R1 | R2 | R3 | R4 | R5 | R6 | R7 | R8 | R9 | R10 | R11 | R12 | R13 | R14 | R15 |
|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|
| 98.7 | 98.2 | 96.2 | 96.2 | 96.2 | 97.1 | 96.5 | 96.3 | 94.9 | 94.6 | 98.3 | 74.7 | 98.3 | 97.2 | 95.8 |
| **Q1** | **Q2** | **Q3** | **Q4** | **Q5** | **Q6** | **Q7** | **Q8** | **Q9** | **Q10** | **Q11** | **Q12** | **Q13** | **Q14** | **Q15** |
| 90.2 | 95.7 | 94.2 | 92.1 | 92.9 | 93.6 | 97.3 | 97.5 | 94.8 | 92.9 | 95.7 | 96.0 | 97.1 | 99.2 | 95.6 |
| **C1** | **C2** | **C3** | **C4** | **C5** | **C6** | **C7** | **C8** | **C9** | **C10** | **C11** | **C12** | **C13** | **C14** | **C15** | **C16** |
| 94.0 | 96.6 | 95.5 | 91.2 | 89.2 | 93.3 | 89.3 | 92.1 | 89.3 | 85.7 | 88.9 | 93.5 | 95.1 | 92.8 | 90.6 | 90.4 |

| TM30 | | | |
|---|---|---|---|
| Hue Bin | $R_f$ | Chroma | Hue |
| 1 | 94 | -1% | 1% |
| 2 | 97 | 0% | -1% |
| 3 | 96 | -1% | -2% |
| 4 | 91 | -5% | -3% |
| 5 | 89 | -8% | -1% |
| 6 | 93 | -5% | 2% |
| 7 | 89 | -6% | 5% |
| 8 | 92 | -2% | 5% |
| 9 | 89 | -1% | 7% |
| 10 | 86 | 1% | 10% |
| 11 | 89 | 4% | 7% |
| 12 | 93 | 3% | 0% |
| 13 | 95 | -1% | -3% |
| 14 | 93 | 3% | -4% |
| 15 | 91 | -1% | -2% |
| 16 | 90 | 1% | -4% |

## LUME-01-SW-DRY-35-6.0HE-ENC/TL

3601 K

**CRI:** 97.3

**CRI R9:** 97.0

**TM30 Rf:** 91.4

**TM30 Rg:** 97.5

**CQS:** 94.8

**X:** 0.402

**Y:** 0.395

**U:** 0.232

**V:** 0.342

**Δuv:** 0.0025










| R1 | R2 | R3 | R4 | R5 | R6 | R7 | R8 | R9 | R10 | R11 | R12 | R13 | R14 | R15 |
|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|
| 98.9 | 99.2 | 97.3 | 96.3 | 96.7 | 97.7 | 96.2 | 96.3 | 97.0 | 97.1 | 98.8 | 75.9 | 98.8 | 97.6 | 96.3 |
| **Q1** | **Q2** | **Q3** | **Q4** | **Q5** | **Q6** | **Q7** | **Q8** | **Q9** | **Q10** | **Q11** | **Q12** | **Q13** | **Q14** | **Q15** |
| 90.2 | 95.8 | 94.2 | 91.9 | 92.5 | 93.5 | 98.1 | 98.6 | 96.0 | 94.8 | 97.4 | 97.3 | 97.9 | 98.6 | 95.3 |
| **C1** | **C2** | **C3** | **C4** | **C5** | **C6** | **C7** | **C8** | **C9** | **C10** | **C11** | **C12** | **C13** | **C14** | **C15** | **C16** |
| 93.9 | 96.5 | 95.7 | 91.2 | 89.2 | 93.4 | 89.2 | 92.0 | 88.9 | 85.5 | 88.8 | 93.2 | 94.6 | 92.7 | 90.5 | 90.3 |

| TM30 | | | |
|---|---|---|---|
| Hue Bin | $R_f$ | Chroma | Hue |
| 1 | 94 | -1% | 1% |
| 2 | 97 | 0% | -1% |
| 3 | 96 | -1% | -2% |
| 4 | 91 | -5% | -3% |
| 5 | 89 | -8% | -1% |
| 6 | 93 | -5% | 2% |
| 7 | 89 | -6% | 5% |
| 8 | 92 | -2% | 5% |
| 9 | 89 | 0% | 8% |
| 10 | 85 | 2% | 10% |
| 11 | 89 | 5% | 6% |
| 12 | 93 | 3% | 0% |
| 13 | 95 | 0% | -4% |
| 14 | 93 | 3% | -4% |
| 15 | 90 | -1% | -2% |
| 16 | 90 | 1% | -4% |

**NOTES:**
- CRI R values, only R1-R8 are used to calculate RA CRI values
- TM30 C values, 16 binned values out of total of 99 C values
- CQS Q values
- Data subject to change, all data has +/- 5% tolerance

© 2024 QTL. All rights reserved | 155 Hill St. Milford, CT 06460 | 203-367-8777 | sales@QTL.lighting | QTL.lighting

Specification subject to change. Rev-03-10-24

# Q-CAP LUME-SW-HE(01)

Flexible Fixtures Color Data

## LUME-01-SW-DRY-40-1.5HE-ENC/TL

4239 K

**CRI:** 97.3

**CRI R9:** 98.2

**TM30 Rf:** 92.0

**TM30 Rg:** 99.4

**CQS:** 94.4

**X:** 0.371

**Y:** 0.371

**U:** 0.221

**V:** 0.332

**Δuv:** 0.0001










| R1 | R2 | R3 | R4 | R5 | R6 | R7 | R8 | R9 | R10 | R11 | R12 | R13 | R14 | R15 |
|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|
| 98.5 | 99.5 | 96.0 | 97.4 | 96.5 | 95.6 | 97.6 | 97.2 | 98.2 | 96.3 | 97.9 | 70.9 | 99.1 | 97.1 | 95.8 |
| **Q1** | **Q2** | **Q3** | **Q4** | **Q5** | **Q6** | **Q7** | **Q8** | **Q9** | **Q10** | **Q11** | **Q12** | **Q13** | **Q14** | **Q15** |
| 92.2 | 98.4 | 89.4 | 87.8 | 91.6 | 94.5 | 97.6 | 98.5 | 97.7 | 98.1 | 98.2 | 99.6 | 99.5 | 98.4 | 96.2 |
| **C1** | **C2** | **C3** | **C4** | **C5** | **C6** | **C7** | **C8** | **C9** | **C10** | **C11** | **C12** | **C13** | **C14** | **C15** | **C16** |
| 94.4 | 96.8 | 96.0 | 92.6 | 91.1 | 95.9 | 93.5 | 92.3 | 88.7 | 86.6 | 86.1 | 93.2 | 94.0 | 94.8 | 89.8 | 89.9 |

| TM30 | | | |
|---|---|---|---|
| Hue Bin | $R_f$ | Chroma | Hue |
| 1 | 94 | -1% | 1% |
| 2 | 97 | 0% | 0% |
| 3 | 96 | 0% | 0% |
| 4 | 93 | -3% | -1% |
| 5 | 91 | -6% | -1% |
| 6 | 96 | -2% | 1% |
| 7 | 94 | -4% | 2% |
| 8 | 92 | -2% | 4% |
| 9 | 89 | -1% | 9% |
| 10 | 87 | 0% | 9% |
| 11 | 86 | 4% | 9% |
| 12 | 93 | 3% | 2% |
| 13 | 94 | 3% | -2% |
| 14 | 95 | 0% | 0% |
| 15 | 90 | 2% | -4% |
| 16 | 90 | 2% | -5% |

## LUME-01-SW-DRY-40-3.0HE-ENC/TL

4218 K

**CRI:** 97.1

**CRI R9:** 98.5

**TM30 Rf:** 91.7

**TM30 Rg:** 99.1

**CQS:** 94.3

**X:** 0.372

**Y:** 0.371

**U:** 0.221

**V:** 0.332

**Δuv:** 0.0002










| R1 | R2 | R3 | R4 | R5 | R6 | R7 | R8 | R9 | R10 | R11 | R12 | R13 | R14 | R15 |
|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|
| 98.5 | 99.5 | 96.2 | 96.8 | 96.2 | 95.5 | 97.4 | 97.1 | 98.5 | 96.2 | 97.5 | 70.3 | 99.1 | 97.2 | 95.7 |
| **Q1** | **Q2** | **Q3** | **Q4** | **Q5** | **Q6** | **Q7** | **Q8** | **Q9** | **Q10** | **Q11** | **Q12** | **Q13** | **Q14** | **Q15** |
| 91.8 | 98.2 | 89.4 | 87.5 | 91.1 | 93.9 | 97.6 | 98.4 | 97.9 | 98.2 | 98.1 | 99.5 | 99.6 | 98.4 | 96.0 |
| **C1** | **C2** | **C3** | **C4** | **C5** | **C6** | **C7** | **C8** | **C9** | **C10** | **C11** | **C12** | **C13** | **C14** | **C15** | **C16** |
| 94.2 | 96.6 | 95.9 | 92.3 | 90.8 | 95.7 | 92.9 | 91.7 | 88.1 | 86.1 | 85.9 | 93.2 | 93.8 | 94.6 | 89.5 | 89.7 |

| TM30 | | | |
|---|---|---|---|
| Hue Bin | $R_f$ | Chroma | Hue |
| 1 | 94 | -1% | 1% |
| 2 | 97 | 0% | 0% |
| 3 | 96 | -1% | 0% |
| 4 | 92 | -3% | -2% |
| 5 | 91 | -6% | -1% |
| 6 | 96 | -2% | 1% |
| 7 | 93 | -4% | 3% |
| 8 | 92 | -2% | 5% |
| 9 | 88 | -1% | 9% |
| 10 | 86 | 0% | 9% |
| 11 | 86 | 4% | 9% |
| 12 | 93 | 3% | 2% |
| 13 | 94 | 3% | -2% |
| 14 | 95 | 0% | 0% |
| 15 | 90 | 2% | -4% |
| 16 | 90 | 2% | -5% |

## LUME-01-SW-DRY-40-6.0HE-ENC/TL

4192 K

**CRI:** 97.2

**CRI R9:** 96.8

**TM30 Rf:** 91.6

**TM30 Rg:** 99.3

**CQS:** 94.3

**X:** 0.372

**Y:** 0.369

**U:** 0.223

**V:** 0.331

**Δuv:** -0.0011










| R1 | R2 | R3 | R4 | R5 | R6 | R7 | R8 | R9 | R10 | R11 | R12 | R13 | R14 | R15 |
|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|
| 98.0 | 99.4 | 96.8 | 97.2 | 96.5 | 95.8 | 97.1 | 96.9 | 96.8 | 98.3 | 98.3 | 71.5 | 98.5 | 97.5 | 95.3 |
| **Q1** | **Q2** | **Q3** | **Q4** | **Q5** | **Q6** | **Q7** | **Q8** | **Q9** | **Q10** | **Q11** | **Q12** | **Q13** | **Q14** | **Q15** |
| 91.8 | 98.3 | 89.5 | 87.7 | 91.3 | 94.3 | 97.8 | 98.5 | 97.9 | 98.3 | 98.1 | 99.4 | 99.9 | 98.0 | 95.7 |
| **C1** | **C2** | **C3** | **C4** | **C5** | **C6** | **C7** | **C8** | **C9** | **C10** | **C11** | **C12** | **C13** | **C14** | **C15** | **C16** |
| 94.0 | 96.4 | 96.0 | 92.3 | 90.7 | 95.7 | 92.9 | 91.5 | 87.9 | 86.3 | 86.1 | 93.3 | 93.7 | 94.6 | 89.5 | 89.6 |

| TM30 | | | |
|---|---|---|---|
| Hue Bin | $R_f$ | Chroma | Hue |
| 1 | 94 | -1% | 1% |
| 2 | 96 | 0% | 0% |
| 3 | 96 | 0% | 0% |
| 4 | 92 | -3% | -2% |
| 5 | 91 | -6% | -1% |
| 6 | 96 | -2% | 1% |
| 7 | 93 | -4% | 3% |
| 8 | 92 | -2% | 5% |
| 9 | 88 | -1% | 9% |
| 10 | 86 | 0% | 9% |
| 11 | 86 | 5% | 8% |
| 12 | 93 | 4% | 2% |
| 13 | 94 | 3% | -2% |
| 14 | 95 | 0% | 0% |
| 15 | 90 | 2% | -4% |
| 16 | 90 | 2% | -5% |

**NOTES:**
- CRI R values, only R1-R8 are used to calculate RA CRI values
- TM30 C values, 16 binned values out of total of 99 C values
- CQS Q values
- Data subject to change, all data has +/- 5% tolerance

© 2024 QTL. All rights reserved | 155 Hill St. Milford, CT 06460 | 203-367-8777 | sales@QTL.lighting | QTL.lighting

Specification subject to change. Rev-03-10-24

# MATERIAL RECYCLING

Q-CAP FLEXIBLE FIXTURES

You may be done with your products, but chances are they still have more to give. Follow these instructions to break down and sort recyclable components. Check with local recycling collection to ensure they accept the materials listed below.

Additionally, Q-Tran offers a Takeback Program. Contact factory for information.




E

Q-CAP Fixture
Wires

© 2024 QTL. All rights reserved | 155 Hill St. Milford, CT 06460 | 203-367-8777 | sales@QTL.lighting | QTL.lighting